

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other2. NAME OF OPERATOR
Energy Reserves Group, Inc.3. ADDRESS OF OPERATOR
P.O. Box 3280, Casper, Wyoming 826024. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1520' FSL & 1520' FEL (NW/SE)
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

☐ TEST WATER SHUT-OFF
☐ FRACTURE TREAT
☐ SHOOT OR ACIDIZE
☐ REPAIR WELL
☐ PULL OR ALTER CASING
☐ MULTIPLE COMPLETE
☐ CHANGE ZONES
☐ ABANDON*(other) Well History

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The above referenced well was drilled w/7-7/8" bit to a T.D. of 6,514' KB & logs ran -

Ran 162 jts. 4-1/2", 10.5#, K-55, Range 3, 8rth, new casing set @ 6,513' KB. Cemented 1st stage w/100 sk Class "B" 50-50 Pozmix w/1/4# Flocele per sk, followed by 335 sk Class "B" cement w/10% Salt + 1/4# Flocele/sk. Cemented 2nd stage w/650 sks 65-35 Pozmix w/6% Gal + 10# Gilsonite/sk, followed by 400 sx Class "B" 50-50 Pozmix w/12-1/2# Gilsonite/sk. Final plug down @ 4:30 PM 11-18-79.
11-19-79 - W.O.C. & W.O.C.T.

Subsurface Safety Valve: Manu. and Type _____

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED _____ TITLE Drilling Foreman DATE 11-19-79

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____ DATE _____

APPROVED

NMOCC

NOV 29 1979

JAMES F. SIMS

DISTRICT OIL & GAS SUPERVISOR

*See Instructions on Reverse Side