

5 - USGS

1 - Pioneer

1 - File

Form 9-331
Dec. 1973Form Approved.
Budget Bureau No. 42-R1424UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other2. NAME OF OPERATOR
PIONEER PRODUCTION CORP.3. ADDRESS OF OPERATOR
Box 208, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1120' FSL - 1800' FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON* ☐(other) ☐

5. LEASE

NM 013365

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Phillips

9. WELL NO.

2E

10. FIELD OR WILDCAT NAME

Basin Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 22 T28N R11W

12. COUNTY OR PARISH

San Juan

13. STATE

NM

14. API NO.


15. ELEVATIONS (SHOW DF, KDB, AND WD)

5635' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

See attached sheet for spud and surface csg.



Subsurface Safety Valve Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Agent

DATE

11-26-80

ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY

DEC 04 1980


TITLE

DATE

CONDITIONS OF APPROVAL IF ANY:

FARMINGTON DISTRICT

NMOCC



dugan production corp.

PIONEER PRODUCTION CORP.
Phillips #2E
1120' FSL - 1800' FWL
Sec 22 T28N R11W
San Juan County, NM

MORNING REPORT

11-25-80 Moved and Rig up Four Corners DRLG. Co. Rig #10. Spudded
12 $\frac{1}{4}$ " hole @ 7:45 p.m. 11-24-80. Drilled to 598'. Now running
8-5/8" csg. 3/4" @ 598'.

8-1/2 hrs - drilling
1-1/2 hrs - trip
1/4 hr - rig service
1-1/2 hrs - drill rat and mouse holes
8-3/4 hrs - MI & RU

11-26-80 1344' - Drlg. Wtr. and Benix 1" @ 1344'
Ran 14 jts 8-5/8" O.D., 24#, K-55, 8Rd, ST&C csg. T.E.
578.51' set @ 590' RKB. Cemented w/ 325 sx class "B" neat plus 2% CaCl P.C.
2% CaCl. P.O.B. @ 8:45 a.m. 11-25-80. (approx. 2 bbls good cement to
to surface)

6-1/4 hrs drilling
1-1/2 hrs trip
1/4 hr rig service
2 hrs run 8-5/8" csg
3/4 hrs cement 8-5/8" csg
12 hrs W.O.C.
1/2 hr test csg and B.O.P.
1/2 hr drlg. cement and shoe
1/4 hr pump repair