

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐  
2. NAME OF OPERATOR  
Dugan Production Corp.  
3. ADDRESS OF OPERATOR  
Box 208, Farmington, NM 87401  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
790' FSL - 790' FEL  
AT SURFACE:  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:  
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE  
NM 25455  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
7. UNIT AGREEMENT NAME  
8. FARM OR LEASE NAME  
Aunt America  
9. WELL NO.  
#1  
10. FIELD OR WILDCAT NAME  
WAW FR PC  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec 32 T28N R13W  
12. COUNTY OR PARISH  
San Juan  
13. STATE  
NM  
14. API NO.  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
5890' GL

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☒

RECEIVED

OCT 6 1982

U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

RECEIVED

OCT 12 1983

OIL CON. DIV.  
DIST. 3

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Plugged and abandoned well as follows:

1. Filled 2-7/8" O.D., 6.4#, 10V, tubing for casing from PBD 1392 to surface, using 38 sx class "B" cement on 9-30-82.
2. No dry hole marker per MMS instructions
3. Filled all pits.
4. Cleaned well location of all equipment, pipe, junk, and trash.
5. Will perform surface restoration as specified by the surface management agency or land owner next planting season.
6. Cut off tie-downs 4' below surface.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Jim L. Jacobs TITLE Geologist DATE 10-5-82

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY: