

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR

SUPRON ENERGY CORPORATION

3. ADDRESS OF OPERATOR

P.O. Box 808, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 790 ft./S ; 1800 ft./W line

AT TOP PROD. INTERVAL: Same as above

AT TOTAL DEPTH: Same as above

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) Ran 4 1/2" casing ☒

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐
☐
☐
☒

RECEIVED

JUN 2 1981

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Drilled 7-7/8" hole w/mud to total depth of 6492 ft. R.K.B. Total depth was reached on 5-26-81.

2. Ran 158 jts. of 4 1/2", 10.50#, K-55 casing and set at 6492 ft. R.K.B. w/float collar at 6448 ft. R.K.B. Stage collars set at 4439 ft. and 1857 ft. R.K.B.

3. Cemented first stage w/350 sx of 50-50 POZ mix w/2% gel & 10% salt. Plug down at 12:15 p.m. 5-29-81. Cemented second stage w/250 sx of 50-50 POZ mix w/4% gel & 6 1/2 lb. of gilsonite per sack & 50 sx of class B w/2% calcium chloride. Plug down @ 3:45 a.m. 5-29-81. Cemented third stage w/125 sx of 65-35-12 w/12 1/2 lb. of gilsonite per sack & 50 sacks of class B w/2% calcium chloride. Plug down at 4:30 a.m. 5-29-81.

4. Ran temperature survey and found cement top at 300 ft. R.K.B.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Kenneth E. Roddy TITLE Production Supt. DATE June 1, 1981

Kenneth E. Roddy

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____ DATE _____

ACCEPTED FOR RECORD

*See Instructions on Reverse Side

JUN 03 1981

FARMINGTON DISTRICT
BY Dean Elliott