-37.5

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

9–331 1973	Form Approved. Budget Bureau No. 42–R1424		
UNITED STATES /	5. LEASE		
DEPARTMENT OF THE INTERIOR	SF-078019		
GEOLOGICAL SURVEY /	6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
	<u>→ 34.75 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 </u>		
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME		
(Do not use this form for proposals to drill or to deepen or plug back to a different	nt		
reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME		
1. oil gas X other	E. H. Pipkin		
well well other	9. WELL NO.		
2. NAME OF OPERATOR	21 新計劃 開業		
Energy Reserves Group, Inc.	10. FIELD OR WILDCAT NAME Kutz Fruitland and West Kutz		
3. ADDRESS OF OPERATOR	Pictured Cliffs		
P. O. Box 3280, Casper, Wyoming 82602	11. SEC., T., R., M., OR BLK. AND SURVEY OR		
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 1	AREA ALLO O SECTION		
below.)	Sec. 35-T28N-R11W		
AT SURFACE: 1,090' FSL & 1,520' FEL (SW/SE)	12. COUNTY OR PARISH 13. STATE		
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	San Juan New Mexico		
	14. API NO. 1		
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE			
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)		
DECUEST FOR APPROVAL TO	1\(\c.1\) - 5,906'; K.B 5,911'		
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT DE			
TEST WATER SHUT-OFF X FRACTURE TREAT			
SHOOT OR ACIDIZE	Harry Ministry		
	(NOTE: Distry results of		
PULL OR ALTER CASING	(NOTE: RedDyt results of multiple completion or zone change on Form 9-830.) 00129 1981		
MULTIPLE COMPLETE			
CHANGE ZONES	OIL CON COM.		
ABANDON*	QIST 3		
(other) Well History X			
17 DESCRIPE PROPOSED OR COMPLETED OPERATIONS (OLD IN			
 DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly st including estimated date of starting any proposed work. If well is 	directionally drilled give subsurface locations and		
measured and true vertical depths for all markers and zones pertin	ent to this work.)*		
The above referenced well was spudded	at 2:30 p.m., 10-15-81.		

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly sta including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine The above referenced well was spudded a

Drilled 9-7/8" hole to 115'. Ran 3 joints-7" O.D., 23#, K-55, R-3, S. T. & C., new casing set at 110'. Cemented w/60 sx. of Calss B cement w/2% CaCl₂ and 1/4 # Flocele/sx. Plugdown at 5:30 p.m., 10-15-81.

W.O.C. NU & press. tested BOPE to 1,000 psi - held o.k.

Drilled 6-1/4" hole to 1,960' and ran logs.

Ran 50 joints - 4-1/2" O.D., 10.5#, K-55, R-3, S.T. & C., new casing set at 1,951'. Cemented w/400 sx. of 50-50 pozmix w/2% gel: 0.5% CFR-2 & 1/4 # Flocele/sx. Plugdown at 8:00 p.m., 10-18-81. Good cement returns. W.O.C.T.

Subsurface Safety Valve: Manu. and Type			Set @		_ Ft.
18. I hereby certify that the foregoing is					
SIGNED Roser Dilley	TITLE Drlg. SuptRMD	DATE _	October 20,	1981	
	(This space for Federal or State office use)			<u> </u>	_
APPROVED BY	TITLE	DATE .			