

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐

2. NAME OF OPERATOR
Amoco Production Company

3. ADDRESS OF OPERATOR
501 Airport Drive, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1090' FNL x 1840' FEL
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) Completion ☐

SUBSEQUENT REPORT OF:

☐ **RECEIVED**
JUN 1 1983
☐ U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

5. LEASE
I-149-IND-8471

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
Navajo Tribe

7. UNIT AGREEMENT NAME
Gallegos Canyon Unit

8. FARM OR LEASE NAME

9. WELL NO.
176E

10. FIELD OR WILDCAT NAME
Basin Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
NW/NE, Section 25, T28N, R13W

12. COUNTY OR PARISH
San Juan

13. STATE
New Mexico

14. API NO.
30-045-25175

15. ELEVATIONS (SHOW DF, KDB, AND WD)
5865' GL

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Completion operations commenced 4-25-83. Total depth is 6330' and plugback depth is 6310'. Pressure test casing to 3800 PSI. Test OK. Perforated intervals 6183'-6189', 6221'-6226', 6232'-6265' with 2 SPF, a total of 88 .38" holes. Fraced interval 6183'-6265' with 105,000 gallons 75 quality N₂ foam containing 20 lbs./1000 gel with 2% KCL and 1 gal/1000 surfactant and 206,000 lbs. 20-40 sand. Landed 2-3/8" tubing 6228' with seating nipple at 6197'. Rig released 5-2-83.

Subsurface Safety Valve: Manu. and Type

Set @

Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED *Ben* TITLE Dist. Admin. Supv DATE 5/26/83

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY

TITLE

DATE

ACCEPTED FOR RECORD

*See Instructions on Reverse Side

NMCCC

JUN 07 1983

FARMINGTON DISTRICT

BY