

## SUNDRY NOTICES AND REPORTS ON WELLS

1. oil well ☒ gas well ☐ other ☐

HICKS OIL &amp; GAS

P.O. BOX 174

AT SURFACE: 700 ' from North line and 1980'  
AT TOP PROD. INTERVAL: From West line.  
AT TOTAL DEPTH:

(other)

RECEIVED

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

U. S. AIR FORCE SURVEY  
FAIRFAC, DE, N. C.

Spudded 12 1/4" hole at 9:00AM 3-15-82. Drilled to 399'. Survey 1<sup>st</sup> at 399'. Ran 9 jts. of 8 5/8"-23# S.T. & C. casing and set at 399' with 275 sks. of class B cement. Circulated 20 bbls. of good cement. W.O.C. 12 hrs. Pressure tested blow out preventer to 1000 psi for 30 minutes. Drilled 50' of hard cement. Proceeded to drill ahead.

Set @ \_\_\_\_\_ Ft.

SIGNED

Mike Hicks

TITLE PRESIDENT

DATE 3-17-82

(This space for Federal or State office use)

TITLE

DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY

ACCEPTED FOR RECORD

\*See Instructions on Reverse Side

# MMOC

22