

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form Approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR
Southland Royalty Company
3. ADDRESS OF OPERATOR
P.O. Drawer 570, Farmington, NM 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1100' FNL & 1800' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐
(other) Perforation & Stimulation X

5. LEASE
SF-075794
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Hughes
9. WELL NO.
#3
10. FIELD OR WILDCAT NAME
Bloomfield Chacra/Kutz Fruitland
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Section 23, T28N, R11W
12. COUNTY OR PARISH
San Juan
13. STATE
New Mexico
14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
5767'

(NOTE: Report results of multiple completions or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6-22-82 Perf'd Fruitland at 1490', 1493', 1496', 1499', 1502', 1552', 1555', 1558'. Total of 8 holes. Perf'd Chacra at 2756', 2758', 2760', 2762', 2764', 28611', 2863', 2869', 2871', 2873', 2875'. Total of 11 holes. Frac'd Fruitland with 10,000 gallons fresh water pad, 28,000 gallons fresh water carrying 1 ppg 20/40 sand.

6-23-82 Frac'd Chacra with 4,000 gallons 70 quality foam pad, with 2% CKL water foamed, 6,000 gallons 70 quality foam with 1 ppg 10/20 sand, 6,000 gallons 70 quality foam with 1-1/2 ppg 10/20 sand, 9,000 gallons 70 quality foam with 2 ppg 10/20 sand, 11,000 gallons 70 quality foam with 2-1/2 ppg 10/20 sand. ATP 3625 psi, AIR 20 bbls, ISIP 1750.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Secretary DATE June 28, 1982

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

NMOCC

JUL 7 1982