

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐
well well other

2. NAME OF OPERATOR
Union Texas Petroleum Corporation

3. ADDRESS OF OPERATOR
P. O. Box 808, Farmington, N.M. 87499

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1793 ft./S; 593 ft./E lines
AT TOP PROD. INTERVAL: Same as above
AT TOTAL DEPTH: Same as above

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐

(other) Drilled to T.D. and cased

5. LEASE

SF 047017-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Angel Peak

9. WELL NO.

29

10. FIELD OR WILDCAT NAME

Undesignated Gallup

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 10, T-28N, R-11W, N.M.P.M.

12. COUNTY OR PARISH 13. STATE

San Juan

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

5591 R.K.B.

RECEIVED

JUL 1 1983

(NOTE) Report results of multiple completions or zone changes on Form 9-330.

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

RECEIVED

JUL 1 1983

PROD. CON. DIV.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Spudded 12-1/4" hole at 10:30 A.M., 6-14-83.
2. Drilled 12-1/4" surface hole to a total depth of 320 ft. R.K.B.
3. Ran 7 joints, 9-5/8", 36.0#, K-55 casing and set at 315 ft. R.K.B.
4. Cemented with 236 cu. ft. Class "B" with 2% CaCl₂. Circulated cement to surface. Plug down at 4:00 P.M., 6-14-83.
5. Wait on cement 11 hours.
6. Pressure tested to 800 PSI.
7. Drilled 8-3/4" intermediate hole with mud to a total depth of 5164 ft. R.K.B.
8. Logged well.
9. Ran 132 joints 7", 23.0#, K-55 casing from surface to 5164 ft. R.K.B., float collar at 5124 ft. R.K.B., DV tool at 1977 ft. R.K.B.

(Over)

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED W. K. Cooper TITLE Field Oper. Mgr. DATE June 29, 1983

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

RECEIVED FOR RECORD

JUL 07 1983

*See Instructions on Reverse Side

NMOCC

SY JK

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO : 1981 O - 347-166

10. Cemented first stage with 1062 cu. ft. 65-35 Poz with 12% gel, 12-1/4# Gilsomite and 1/4# Flocele per sack followed by 118 cu. ft. Class "B" with 2% CaCl₂. Cemented second stage with 918 cu. ft. 65-35 Poz with 12% gel, 12-1/4# Gilsomite and 1/4# Flocele per sack followed by 118 cu. ft. Class "B" with 2% CaCl₂. Circulated 1 bbl. cement to surface. Plug down at 12:00 P.M., 6-19-83.
11. Wait on cement 9 hours.
12. Drilled DV tool and pressure tested casing to 1500 PSI.
13. Drilled 6-1/4" hole with natural gas to a total depth of 6140 ft. R.K.B.
14. Logged the well.
15. Ran 27 joints 4-1/2", 11.6#, N-80 casing as liner. Bottom set at 6140 ft. R.K.B., top at 4960 ft. R.K.B., float collar at 6094 ft. R.K.B.
16. Cemented with 206 cu. ft. 50-50 Poz with 2% gel, 0.6% FLA, 1/4# Flocele and 10# salt per sack. Plug down at 4:30 A.M., 6-22-83. Reversed out 15 bbls. cement.