

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well ☐ gas well ☐ other

2. NAME OF OPERATOR
Union Texas Petroleum Corporation

3. ADDRESS OF OPERATOR
P. O. Box 808, Farmington, N.M. 87499

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1721 ft./South; 1919 ft./West
AT TOP PROD. INTERVAL: Same as above
AT TOTAL DEPTH: Same as above

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

☐
☐
☐
☐
☐
☐
☐
☐

(other) Drilled to T.D. and Cased

5. LEASE
NM 020982
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Mangum
9. WELL NO.
5
10. FIELD OR WILDCAT NAME
Undesignated Gallup
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 10, T-28N, R-11W, N.M.P.M.
12. COUNTY OR PARISH
San Juan
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
5514' R.K.B.

(NOTE: Report results of multiple completion or zone change on Form 9-331-C)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work:)*

1. Spud 12-1/4" surface hole at 10:00 P.M., 6-30-83.
2. Drilled 12-1/4" hole to TD of 312' R.K.B.
3. Ran 7 joints of 8-5/8", 24.0#, K-55 casing and set at 307' R.K.B.
4. Cemented 8-5/8" with 330 cu. ft. Cl B w/3% CaCl₂ and 1/4# Flocele per sack. Cement circulated. Wait on cement.
5. Pressure tested to 800 PSI. Held OK.
6. Drilled 7-7/8" hole to T.D. of 6073' R.K.B. on 7-9-83. Logged well.
7. Ran 144 joints 5-1/2", 15.50#, K-55 casing and set at 6070' with 1st DV tool at 4370' and 2nd DV tool at 1886' R.K.B.
8. Cemented 5-1/2" 1st stage with 640 cu. ft. 50-50 Poz w/2% gel, 0.6% FLA, 1/4# Flocele and 10# salt per sack. Cemented 2nd stage with 1280 cu. ft. 65/35 Poz w/6% gel and 10# Gilsonite per sack followed by 118 cu. ft. Cl B

Subsurface Safety Valve: Manu. and Type _____ Set @ (Over) _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED J. A. Edmister

TITLE Engr. Analyst

DATE 9-16-83

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

ACCEPTED FOR RECORD

*See Instructions on Reverse Side

SEP 21 1983

FARMINGTON RESOURCE AREA

BY 6-83

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO : 1981 0 - 347-166

- w/2% CaCl₂ and 1/4# Flocele per sack. Cemented 3rd stage with 1148 cu. ft. 65/35 Poz w/12% gel and 12-1/2# Gilsontite per sack followed by 118 cu. ft. Cl B w/2% CaCl₂ and 1/4# Flocele per sack. Cement circulated. Wait on cement.
9. Clean out casing to 6018' R.K.B.

RECEIVED