Form 3160-5 (November 1983) (Formerly 9-331) UNITED STATES SUBMIT IN TRIPLICATE* (Other Instructions on re- BUREAU OF LAND MANAGEMENT	Budget Bureau No. 1004-0135 Expires August 31, 1985 5. LEASE DESIGNATION AND SERIAL NO. SF-078828
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
I JUL	7. UNIT AGREEMENT NAME
OIL CAS X OTHER	Gallegos Canyon Unit
2. NAME OF OPERATOR	8. FARM OR LEASE NAME
Energy Reserves Group, Inc.	
3. ADDRESS OF OPERATOR	9. WELL NO.
P. O. Box 3280 Casper, Wyoming 82602	352
4. LOCATION OF WELL (Report location clearly and in accordance with any State sequirements.	10. FIELD AND POOL, OR WILDCAT
At surface	West Kutz Pictured Cliffs
900' FNL & 820' FEL (NE/NE) UL 22 1985	11. SEC., T., B., M., OR BLK. AND SURVEY OR ARMA
HIREAU OF LAND And	Section 14 T28N-R12W
BUREAU OF LAND MANAGEMENT FARMINGTON RESOURCE AREA	
14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH 13. STATE
G.L. 5579' K.B. 5587'	San Juan New Mexic
16. Check Appropriate Box To Indicate Nature of Notice, Report, or Ot	har Data
	NT REPORT OF:
NOTICE OF INTENTION TO:	NT EMPORT OF:
TEST WATER SHUT-OFF PULL OR ALTER CASING WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREAT MULTIPLE COMPLETE FRACTURE TREATMENT	ALTERING CASING
SHOOT OB ACIDIZE ABANDON* SHOOTING OR ACIDIZING	ABANDONMENT*
REPAIR WELL CHANGE PLANS (Other) Well History	y X X f multiple completion on Well
Completion or Recomplet	tion Report and Log form.)
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, in proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical nent to this work.) *	
The above referenced well was spudded at 2:45 P.M. 7-15-85. Drille Set 3 jts 8 5/8", 24#, K-55 ST&C, R3, new casing at 130.72' K.B. C Class "B" cement w/2% CaCl ₂ and 1/4# Flocele/sx. Plug down 9:15 P. returns. Nippled up and pressure tested BOPE to 500 psi-Held O.K. 1580' and ran logs. Ran 38 jts 4 1/2", 10.5#, K-55 ST&C, R3, new Cemented w/250 sx (315 ft ³) 50-50 Pozmix and cement w/2% gel, 0.5% Celloflakes/sx. Plug down at 4:00 P.M. 7-17-85. Good cement returns	emented w/100 sx (118 ft ³) M. 7-15-85. Good cement Drilled 6 1/4" hole to casing set @ 1576.93' K.B. D-31 and 1/4#
7-18-85 W.O.C. and W.O.C.T.	
	AUG 1= 1975 OIL CON, OT! AUG 1= 1975
18. I hereby certify that the foregoing is true and correct	

*See Instructions on Reverse Side

11000000

TITLE _

N. D. Thomas

(This space for Federal or State office use)

APPROVED BY CONDITIONS OF APPROVAL, IF ANY:

STK-

DATE _