Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED Budget Bureau No. 1004-0135 . Expires: March 31, 1993

5. Lease Designation and Serial No.

SUNDRY NOTICES AND RE	PORTS ON WELLS	Š
-----------------------	----------------	---

SF078673

6. If Indian, Allottee or Tribe Name

	rill or to deepen or reentry to a different reservoir. R PERMIT—" for such proposals	
SUBMIT	T IN TRIPLICATE	7. If Unit or CA, Agreement Designation
3. Address and Telephone No.	PRODUCTION COMPANY 87499 (505)325-6900 Description)	8. Well Name and No. SCHLOSSER #97 9. API Weil No. 30-045-29482 10. Field and Pool, or Exploratory Area BASIN FRUITLAND COAL 11. County or Parish, State SAN JUAN COUNTY, NM
	(s) TO INDICATE NATURE OF NOTICE, REPOR	· · · · · · · · · · · · · · · · · · ·
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of Intent Subsequent Report Final Abandonment Notice	Abandonment Recompletion Plugging Back Casing Repair Altering Casing Other SPUD & SET SURFACE CASING	Change of Plans New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Weil Completion or Recompletion Report and Log form.)
	If pertinent details, and give pertinent dates, including estimated date of starting call depths for all markers and zones pertinent to this work.)* IDNITIG DEDODT	any proposed work. If well is directionally drilled

1/ 1 1/1		
4. I hereby certainly that the toragoing is to e and correct Signed	Tide AGENT-PETROLEUM ENGINEER	Date 10/6/97
(This space for Federal or State office use)		ACCEPTED FOR RECORD
Approved by	Tide	Date

M&G DRILLING COMPANY SCHLOSSER #97 623 FSL & 1347 FWL SESW, SECTION 34, T28N R11W SAN JUAN COUNTY, NEW MEXICO

DRILLING REPORT

Move in and rig up L&B Speed Drill. Spud 8 $\frac{3}{4}$ " surface hole and drill to 125 ft. Circulate hole clean and trip out of hole. Run 3 joints 7" 23# J-55 new surface casing set at 122 ft 10-2-97 GL and centralized at 80 ft and 40 ft. Cemented surface with 50 sx (59 ft3) of Class B cement containing 2% CaCl and ¼# celoflake per sack. Good circulation throughout job.

Circulated 3 barrels of good cement to surface. Plug down at 6:00 pm 10-2-97. SDFN