

submitted in lieu of Form 3160-5

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator
SOUTHLAND ROYALTY

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
810' FSL, 870' FEL Sec. 15, T-28-N, R-13-W, NMPM

Lease Number
NM-09979
6. If Indian, All. or
Tribe Name
7. Unit Agreement Name
8. Well Name & Number
Robinson #3
9. API Well No.
10. Field and Pool
Basin Dakota
11. County and State
San Juan Co, NM

RECEIVED

JAN 28 1994

OIL CON. DIV
DIST. 3

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment

Type of Action

☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other -
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut off
☐ Conversion to Injection

13. Describe Proposed or Completed Operations

01-13-94 MOL&RU. Kill well. TOOH w/tbg. Set cmt ret @ 6237'. PT tbg 1500#/5 min, ok. Sting out. PT csg 400, 0.5 bbl/min leak. Sting into ret. Est rate. Pressured to 1500 psi w/no rate. Consult w/BLM. Spot 7 sx Class "B" cmt on top of ret. Pull up to 6047'. Spot 9 bbl 9# 50 vis mud 6047-5445'. Pull up to 5447'. Spot 12 sx Class "B" cmt. TOC @ 5284'. Pull up to 5157'. Reverse circ. WOC.
01-14-94 TIH, tag TOC @ 5287'. Pull up to 5280'. Spot 30 bbl 9# 50 vis mud 5280-3320'. Load hole. PT csg, pressure to 400 psi, 0.5 bbl/min leak. Perf csg @ 3320'. Set cmt ret @ 3282'. Est rate. PT csg 400#, 0.5 bbl/min leak. Sting into ret. Pump 43 sx Class "B" cmt below ret and 7 sx Class "B" above ret. TOC @ 3187'. Pull up to 3092'. Spot 20 bbl 9# 50 vis mud 3092-1790'. Pull up to 1788'. Spot 24 sx Class "B" inside plug 1788-1460'. Pull up to 1471'. Reverse circ hole. TOC @ 1471'.
01-15-94 TIH, tag TOC @ 1575'. Perf @ 1450'. Set cmt ret @ 1408'. Spot 48 sx Class "B" cmt below ret, 6 sx above ret. TOC @ 1318'. Pull up to 1217'. Spot 11 bbl 9# 50 vis mud 1217-530'. PT csg 500#/5 min, ok. Perf csg @ 530'. Est rate. Spot 174 sx Class "B" cmt down csg and back to surface thru bradenhead. ND BOP. Cut off WH. Install dry hole marker. Released rig. Well plugged & abandoned.

Approved as to accuracy of the data.
Liability for the information on
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Affairs Date 1/17/94

(This space for Federal or State Office use)

APPROVED BY _____ Title _____

CONDITION OF APPROVAL, if any:

APPROVED

JAN 24 1994

DISTRICT MANAGER

NMOCD