1-L.-G. Truby
1-W. R.Johnston
1-Wayne Smith
1-File

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Revised 12-1-55

Pool	Blanc	20	<u> </u>	'ormation	Mes	Everde		_County	Rio A	rriba		
Initial xx Annual								Date of Test 3-27-57				
	pany Pacifi											
Unit	: <u> </u>	ec <u>33</u>	qwT	29 Rg	. <u>ş</u>	6 Purc	haser Pa	cific Nor	thwest	Pipeline Corp.		
	ing 5 1/2 W											
Fu b:	ingW	t	I.D.	Se	t e.t	Pe	rf		To			
	Pay: From_									•		
Producing Thru: Casing Tubing XX Type Well Single Single-Bradenhead-G. G. or G.O. Dual												
Date	e of Complet	ion:		Packe:	r	Sin no	gle-Brade Reservo	enhead-G. oir Temp	G. or (i.O. Dual		
						ED DATA						
T=C Tested Through (Prefer) (Choke) (Mester) Type Taps												
			w Data	Dice	n	Tubing	Data Temp.	Casing D		Duration		
٥.oV		(Orific	e)	Diff.	•				o _F .	of Flow		
SI	Size	Size	e psig	h _w	o _F .			psig	F.	Hr.		
1. 2.		3/4	1410		63	1087	63	968		3		
2. 3.									 			
4. 5.												
<u>5. l</u>						ļ		L	l			
- -	Coefficient				FLOW CALCULATIONS ressure Flow Temp. Gra			rity Compress. Rate of Flow				
No.	No.				Fac		Factor	Factor		Q-MCFPD @ 15.025 psia		
	(24-Hour) √ 12.3650		hwpf	psia 452	•9971		F _g	Fpv 1.047		5606		
1. 2. 3. 4.					-721-							
3 _e												
5.												
ravi	Liquid Hydro ity of Liqui	d Hydroc	carbons		cf/bbl.	CALCUL ATI	Speci Speci		ty Flow	arator Gas wing Fluid 1207.8		
Ŭ 												
No.	P _w	$P_{\mathbf{t}}^2$	F _c Q	(F _c Q) ²	(F	(cQ) ² -e-s)	980 P _w 2	$P_c^2 - P_w^2$	1	Pw Pc		
1. 2.	- 0 (PD10)						60.4	247.4		4.88		
2. 3.			ļ									
4.												
5.					i			<u> </u>				
Absolute Potential: 18,406 MCFPD; n75/3.2832 COMPANY Pacific Northwest Pipeline Corporation												
ADDRESS Loss West Breedyny, Farmington, New Mexico												
AGE	NT and TITLE NESSED	C. R. I	lagner - i	ell Test	Engheer	<u> </u>		APR 1	1007			
	PANY								1957			
					RE N	MARKS		OIL CON. DIST	COM.	/		

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q = Actual rate of flow at end of flow period at W. H. working pressure (P_w). MCF/da. @ 15.025 psia and 60° F.
- P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- Pw Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- hw Differential meter pressure, inches water.
- Fg Gravity correction factor.
- F_t Flowing temperature correction factor.
- F_{DV} Supercompressability factor.
- n I Slope of back pressure curve.

Note: If $P_{\rm W}$ cannot be taken because of manner of completion or condition of well, then $P_{\rm W}$ must be calculated by adding the pressure drop due to friction within the flow string to $P_{\rm t}$.

OIL CONSERVATION COMMISSION										
AZTEC DISTRICT OFFICE										
No. Copies Received 3										
DISTRIBUTION										
NO. FURNISHED										
1 <u> /</u>										
•	ļ									
1										
\	-									
	-									
	RICT OFFICE ved 3 BUTION									