



(SUBMIT IN TRIPLICATE)

 UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
Land Office Santa FeLease No. 2-00146Unit 1-0

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	<u>sub. report of all completion</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

well 17, 1956Well No. 52-34 is located 990 ft. from N line and 1650 ft. from E line of sec. 34R. 1/4 S. 1/4
(1/4 Sec. and Sec. No.)2-N
(Twp.)6-E
(Range)S. 1/4
(Meridian)Blanco Mesa Verde
(Field)San Juan
(County or Subdivision)The elevation of the derrick floor above sea level is 6374.5 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casing; indicate mudding jobs, cementing points, and all other important proposed work)

Total depth 5609' and ran Lane bulls logs. Perf. 5602-5602, 5573-5570, 5560-5556, 5552-5544, 5542-5538, 5536-5530, frac by Dowell w/40,300 gals water only. BD 1300', avg 1350', max 2500', final 1350', went to vacuum. I.P. 46 BPM.

Set SF # 5514 and perf. 5506-5490, 5486-5464, 5456-5446, 5442-5434, frac U-I by Dowell w/4,720 gals water and 35,500 lb sand. BD 1200', avg 1700', max 2400', final 2000', went to vacuum. I.P. 44.2 BPM. Set SF # 5474 and perf. 5306-531, 5344-534, 5336-5332, 5242-5274, 5274-5270, 5242-5234, 5218-5214, 521-5206, 5204-5191, 5194-5186, frac benefited by Dowell w/32,600 gals water only. BD 1000', avg 1000', max 1000', final 1000', went to vacuum. I.P. 34.1 BPM. Set SF # 5114 and perf. 5113-5104, 5086-5082, 5073-5074, 5074-5066, 5054-5048, frac CR by Dowell w/40,5000 gals water only. BD 800', avg 1200', max 2000', final 725'. Standing zero after 5 minutes. I.P. 44.2 BPM. Cleaned to Total depth and ran 5574.95' of

I understand the above plan of work must comply with all regulations of the Geological Survey before operations may be commenced.

Company Selfis Northwest Pipeline Corp. 2-4-56.Address 4135 N. Main,Farmington, New MexicoBy Original signed by T. A. DuganTitle District Engineer