


(SUBMIT IN TRIPLICATE)

Land Office Santa Fe
Lease No. 070282
Unit San Juan 29-5



UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 6 1959, 1959

Well No. 32-29 (10) is located 970 ft. from S line and 1500 ft. from W line of sec. 29
SW/4 Sec. 29 29N 7W N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Blanco M. V. & Wildcat Dakota Rio Arriba New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6531 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

On 7-4-59 Total Depth 3653'.
Ran 96 joints 9 5/8", 36.00#, J-55 casing (3636') set at 3645'. Two stages
cementing tool at 2662'. First stage 115 sacks regular cement, 115 sacks
Pomix with 4% gel & 50 cu. ft. Strata-Crete "6" followed with 50 sacks
Neat cement. Second stage 375 sacks regular cement, 375 sacks Pomix with
6% gel & 2% Calcium Chloride, followed by 50 sacks neat w/2% Calcium Chloride.
Cement circulated on both stages.

Held 1000#/30 minutes.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company El Paso Natural Gas Company

Address Box 997
Farmington, New Mexico

By Original Signed F. H. WOOD

Title Petroleum Engineer

