Form 9-381 (Feb. 1951)	B

1		
	· 	 -

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land	Office	Feat	A Po	
Lease	No. Q	79033		
linie	San	James	20.5	Their

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT	REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS.	1 11	REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SH	HUT-OFF SUBSEQUENT	REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR R		REPORT OF RE-DRILLING OR REPAIR	
OTICE OF INTENTION TO SHOOT OR ACIE		REPORT OF ABANDONMENT	
IOTICE OF INTENTION TO PULL OR ALTER		ARY WELL HISTORY	
OTICE OF INTENTION TO ABANDON WELL	***************************************	• • • • • • • • • • • • • • • • • • •	
(INDICATE AB	OVE BY CHECK MARK NATURE OF REPORT	T, NOTICE, OR OTHER DATA)	X
		June 26	, 19.
	990 ft. from S line and	ft. from w line of sec.	23
3N Sec. 23 (1/4 Sec. and Sec. No.)	23 4 3 V	N.M.P.M.	
Blanco	(Twp.) (Range)	(Meridian)	
(Field)	(County or Subdivision)	(State or Territory)	
17-58. Total Depth 620	XV'. COTO 6168'. Note	gths of proposed casings; indicate mudding jo posed work)	bs, cem
17-58. Total Depth 620 rf. int. 5984-6008; 601	tive sands; show sizes, weights, and length ing points, and all other important property. COTD 6168'. Wate 16-6088; 6044-6060; 606 and 30,000 sand. BI 190-1400-1550-2200-1750 acts balls (17 balls)	gths of proposed casings; indicate mudding jo posed work) Fractured Foint Lockout 0-6092; 6104-6120 (2 SFF) P 12006, max. pr. 30006,	bs, cem
17-58. Total Depth 620 rf. int. 5984-6008; 601 th 91,140 gallons water g. tr. pr. 1150-1200-13 me gallons. Injected 7	tive sands; show sizes, weights, and length ing points, and all other important property. COTD 6168'. Wate 16-6088; 6044-6060; 606 and 30,000 sand. BI 190-1400-1550-2200-1750 acts balls (17 balls)	gths of proposed casings; indicate mudding jo posed work) or fractured Foint Lockout 0-6092; 6104-6120 (2 577) P 12007, max. pr. 30007, J. I.B. 53.5 BPM. Flush	bs, cen
17-58. Total Depth 620 of int. 5984-6008; 601 th 91,140 gallons water g. tr. pr. 1150-1200-13 me gallons. Injected 1	tive sands; show sizes, weights, and length ing points, and all other important property. COTD 6168'. Wate 16-6088; 6044-6060; 606 and 30,000 sand. BI 190-1400-1550-2200-1750 acts balls (17 balls)	gths of proposed casings; indicate mudding jo posed work) or fractured Foint Lockout 0-6092; 6104-6120 (2 577) P 12007, max. pr. 30007, J. I.B. 53.5 BPM. Flush	bs, cem
17-58. Total Depth 620 of int. 5984-6008; 601 th 91,140 gallons water g. tr. pr. 1150-1200-13 me gallons. Injected 1 t. Released balls and	tive sands; show sizes, weights, and length ing points, and all other important property of the content of the	gths of proposed casings; indicate mudding jo posed work) F fractured Foint Lockout D-6098; 6104-6120 (2 877) F 12007, max. pr. 30007, F. I.R. 53.5 RPM. Flush set). Balled off on last	
17-58. Total Depth 620 off. int. 5984-6008; 601 th 91,140 gallons water g. tr. pr. 1150-1200-13 me gallons. Injected 1 t. Released balls and	tive sands; show sizes, weights, and length ing points, and all other important properties of the points, and all other important properties of the points, and all other important properties of the points of the	gths of proposed casings; indicate mudding jo posed work) or fractured Foint Lockout 0-6092; 6104-6120 (2 577) P 12007, max. pr. 30007, J. I.B. 53.5 BPM. Flush	
17-58. Total Depth 620 rf. int. 5984-6008; 601 th 91,140 gallons water g. tr. pr. 1150-1200-1; ne gallons. Injected 1 t. Released balls and understand that this plan of work must pany 21 Page Ratural	tive sands; show sizes, weights, and length ing points, and all other important properties of the points, and all other important properties of the points, and all other important properties of the points of the	gths of proposed casings; indicate mudding jo posed work) F fractured Foint Lockout D-6098; 6104-6120 (2 877) F 12007, max. pr. 30007, F. I.R. 53.5 RPM. Flush set). Balled off on last	
17-58. Total Depth 620 rf. int. 5984-6008; 603 th 91,140 gallons water g. tr. pr. 1150-1200-13 me gallons. Injected 1 t. Released balls and understand that this plan of work must apany 21. Page Batural	tive sands; show sizes, weights, and lengthing points, and all other important projects of the content of the c	gths of proposed casings; indicate mudding jo posed work) F fractured Foint Lockout D-6098; 6104-6120 (2 877) F 12007, max. pr. 30007, F. I.R. 53.5 RPM. Flush set). Balled off on last	enced.
17-58. Total Depth 620 rf. int. 5984-6008; 601 th 91,140 gallons water g. tr. pr. 1150-1200-1; ne gallons. Injected 1 t. Released balls and understand that this plan of work must npany 21 Page Batural ress 800 977	tive sands; show sizes, weights, and lengthing points, and all other important projects of the content of the c	gths of proposed casings; indicate mudding jo posed work) F fractured Foint Lockout D-6098; 6104-6120 (2 207) P 12007, max. pr. 30006, I.R. 53.5 RPM. Plush set). Balled off on last JUL 1 1958 Ott CON. CON. Degical Survey before openiations may be comm	enced.