Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED				
Budget Bure	eau No.	1004-0135		
🗦 Ехриеs:	March	31, 1993		

SUNDAT	NOTICES	AND	REPORTS	ON	WELLS
	-				

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals

5. Lease Designation and Serial No. 6 Afladian. Allottee or Tribe Name

O7c	FAR	
SUBMIT IN TRIPLICATE	Agreement Designation	
1. Type of Well Oil Well X Well Other 2. Name of Operator	San Juan 29-5 Unit 8. Well Name and No. #39	
5. Address a. 4 Telephone No.	9 API Well No. 30-039-07570 10. Field and Pool, or Exploratory Area Blanco Mesa Verde 11. County or Parish. State	
Linit 14 990 FST s. 700 FTTT		
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT	Rio Arriba, NM	
TYPE OF SUBMISSION TYPE OF ACTION	I, OH OTHER BATA	
Notice of Intent Abandonment Recompletion Plugging Back	Change of Plans New Construction	
MAR 0 7 1994 Casing Repair Final Abandonment Notice Altering Casing	Non-Routine Fracturing Water Shut-Off Conversion to Injection	
OIL CON. DIV TP&A	Dispose Water	

(Note: Report results of multiple completion on Well 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled. give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.

2-3-94

MIRU Drake 28 to TP&A well. Bled tbg down-pumped produced H₂O down tbg and csg. ND WH & NU BOP, tested BOP to 3000 psi-Held OK. POOH Laving down 2-3/8" tbg & Guiberson Uni-packer. Inspected tbg-good condition. PU & RIH w/4-3/4" bit and scraper on 2-7/8" workstring to 3275. Drain up. PU & RIH w/remaining 2-7/8" tbg & BHA to PRTD @ 6150'. Pumped 230 bbls produced water down tbg. Unable to circulate. POOH w/2-7/8" workstring, lay down BHA. RU Blue Jet. RIH w/5-1/2" drillable CIBP on wireline set @ 5950'. RIH 2 times w/dump bailer on wireline. Pump 5 sx Class "B" cement on CIBP. POOH. RIH w/2-7/8" open ended tbg to 5800'. Loaded csg & tbg w/lake water mixed w/Tretolite KW-37, 1 drum KW-37 per 100 bbls lake water. Test CIBP to 500 psi (Held ok), cmt & csg held (OK). POOH laying down 100 jts 2-7/8" tbg. Drain-up. POOH laying down remaining 86 jts 2-7/8" tbg. ND BOP. NU WH. Test WH valve to 1000 psi (held ok). SI well. RD and released rig @ 1200 hrs. on 2-6-94.

I hereby certify that the foregoing is true and correct		
Signed	Title	Date
Approved by Ed Hasely Conditions of approval, if any:	Environmental Engineer	2-16-94 A PPROVED
e 18 U.S.C. Section 1001, makes it a crime for any person knowing epresentations as to any matter within its jurisdiction.	gly and willfully to make to any department or agency of the U	nited States any lass. Stictution or fraudulent statements