NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Revised 12-1-55

Poo	l Re	166		Formation	1	Moon Vo	zde	County_	Rie .	Arriba
	tial									
Com	pany	The Boundary	MT PLP	MATER .	Lease	San Jje	m 29-6	We	ll No	kz-ek
	<u> </u>									
Cas	ing 🐕 1	Wt	I.D	Se	t at 60	90¹ P	erf 59 .	56'	То	54581
Tubi	ing 1-1/4"	Nt	_I.D	Se	t at 59	18 1 P	erf		_To	
	Pay: From									
Prod	lucing Thru:	Casing_		Tu	bing 🕱	X X	Type W	ell sing	le .	
Date	of Complet	ion: 6-15	-58	Packe	r	Sir	ngle-Brad Reserv	enhead-G. oir Temp.	G. or	G.O. Dual
						ED DATA				
[e s t	ed Through	(4444)	(Choke)	(HHHH)	Shut 1	in 10 da	y a	Туре Тар	os_	
		Flow	Data			Tubing	Data	Casing D	ata	T
No.	(Line)	(Choke) (Orifice)						Press.	Temp.	of Flow
SI	Size	Size	psig	h _w	°F.	psig	o _F ,	psig	°F∙	Hr.
l.		3/4"	156		27.0	136	210	1101		3
2 . 3.			-						ļ	
٠.				 			 	 	 	
5.										
	(24-Hou	r) \sqrt{h}	wpf	psia Fac psia F		tor Factor		Factor F _{pv}		Rate of Flow Q-MCFPD @ 15.025 psia
										
<u>. l</u>				PRE	SSURE CA	LCU'ATI	ons			
	lquid Hydrod y of Liquid	i Hydrocari			cf/bbl. deg.		Speci Speci ^P c—	fic Gravit	y Flow	rator Gas ving Fluid
	P _w	P _t ² I	F _c Q	$(F_cQ)^2$	(F _c	Q) ² e ^{-s})	P _w 2	P _c -P _w ²	Ca F	P _w P _c
<u>:</u>							1016.5	198.3		5.44
•										
									1	
OMPA ODRE	SS NAME OF	i palenting of Branch	y, Jan	dades.	MCFPD;	.00	/ 4.0496			
LTNE	and TITLE_ SSED_	We do the	24.F - 1	bill foot	ENG! NO.	*		1 mm 2 mm 7 mm 7 mm 7 mm 7 mm 7 mm 7 mm	<u> </u>	
OMPA	NY				REMA	RKS		10F		
							Š	MLUL	F A Ta	
							1	JUL1 OIL COI	4 C	
								DIS		

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q I Actual rate of flow at end of flow period at W. H. working pressure (Pw). MCF/da. @ 15.025 psia and 600 F.
- P_c= 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- Pw Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- hw Differential meter pressure, inches water.
- FgI Gravity correction factor.
- Ft Flowing temperature correction factor.
- F_{pv} Supercompressability factor.
- n I Slope of back pressure curve.

Note: If $P_{\mathbf{W}}$ cannot be taken because of manner of completion or condition of well, then $P_{\mathbf{W}}$ must be calculated by adding the pressure drop due to friction within the flow string to $P_{\mathbf{t}}$.

