

2-Phillips (welcast, Culender)  
1-Confidential  
NEW MEXICO OIL CONSERVATION COMMISSION

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. <b>8-286</b>
7. Unit Agreement Name <b>San Juan 29-6</b>
8. Farm or Lease Name <b>San Juan 29-6 Unit</b>
9. Well No. <b>94</b>
10. Field and Pool, or Wildcat <b>Basin Dakota</b>
12. County <b>Rio Arriba</b>

### SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- 2. Name of Operator <b>Wata Development Co.</b> 3. Address of Operator <b>234 Petroleum Club Plaza, Farmington, New Mexico</b> 4. Location of Well UNIT LETTER <b>M</b> FEET FROM THE <b>South</b> LINE AND <b>1190</b> FEET FROM THE <b>East</b> LINE, SECTION <b>16</b> TOWNSHIP <b>29 N</b> RANGE <b>6 E</b> NMPM. 15. Elevation (Show whether DF, RT, GR, etc.) <b>6463.8' GR</b>
---

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

#### NOTICE OF INTENTION TO:


PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

#### SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9-21-65 Moved in, rigged up rotary rig.  
9-22-65 Spudded in 12 1/4" surface hole @ 2:45 AM Sept. 23, 1965. Finished hole @ 6:45 AM.  
9-23-65 Ran 9 jts. 288' @ 3/8" 24# J-55 STAG csg set @ 302'. Cemented w/175 on req + 2% calcium chloride. PD @ 9:30 AM. JOC 12 hours. Tested csg to 6000 for 30 minutes, hold OK.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Original signed by:  
JOHN T. HAMPTON  
SIGNED \_\_\_\_\_ TITLE **Manager** DATE **10-11-65**

Original Signed Emery C. Arnold  
APPROVED BY \_\_\_\_\_ TITLE **Supervisor Dist # 8** DATE **OCT 15 1965**

CONDITIONS OF APPROVAL, IF ANY: