NO. OF COPIES RECO DISTRIBUTION SANTA FE FILE U.S.G.S.		3-OCC, 1-Comm.F 2-Phillips (Wol 1-Canfield, 1-I NEW MEXIC	lgast-Cull		ISSION	Form C-193 Supersedes Old C-102 and C-103 Effective 1-1-65 5a. Indicate Type of Lease
OPERATOR						State X Fee. 5. State Oil & Gas Lease No.
(DO NOT USE	SUNDR	Y NOTICES AND RE	PORTS ON A	WELLS	RESERVOIR.	NAE - 289
i.	GAS WELL	OTHER-	2-101) FOR SUCH	PROPOSALS.)		7. Unit Agreement Name San Juan 29-6
2. Name of Operator Beta Development Co.						8. Farm or Lease Name Sor Jura 29-6 unit 9. Well No.
3. Address of Operator 234 Petr. Club Plaza, Farmington, N. M.						93
4. Location of Well	В 8	60 FEET FROM THE	North	LINE AND 1695	FEET FROM	10. Field and Pool, or Wildcat Basin Dakota
THEEast	LINE, SECTI	on 16 towns	HIP 29N	RANGE	6W NMPM.	
			Show whether I	F, RT, GR, etc.)		12. County Rio Arriba
10.		Appropriate Box To				er Data
PERFORM REMEDIAL TEMPORARILY ABAND PULL OR ALTER CAST	ои 🔲	PLUG AND Change P		REMEDIAL WORK COMMENCE DRILLIN CASING TEST AND COTHER PET		ALTERING CASING PLUG AND ABANDONMENT
17. Describe Propos work) SEE RUL		perations (Clearly state al	l pertinent deta	ils, and give pertin	ent dates, including	estimated date of starting any proposed
	5967. Found top 1 hr & cle	of cement @ 7450 aned hole. Pres	o & drld	630° solid to 4000# h	cement to 80 eld OK. Spo	rld DV tools @ 3677 & 80°. Circ on bottom tted 750 gals 15% reg
10-23 -65	acid on bottom, displaced hole w/1% potassium chloride wtr. POH. Log TD 8082°. Perf. 8024-30, 8034-40 w/4 JPF & 8070-76° w/2 JPF. SWF w/12,000# 20-40 sd, 16,000 gals treatment wtr., 23,000 gals tot. wtr. FBD from 1900# bask to 1700# w/acid on perfs. TP 4000#, ATP 3600# @ 37 BPM, SI 2000#, 10 MSI 1600#. Perf 7976-88 w/4 JPF. Pumped 500 gals 15% reg acid ahead of frac. SWF w/22,000# 20-40 sd, 56,000 gals 1% potassium chloride wtr., 63,000 gals tot. wtr. TP 4000#, ATP 3950# @ 27 BPM, SI 2600#, 10 MSI 2100#. Pressured down to 1200# in 4 hrs, opened well, WIH w/bit & CO to 8080°. Pulled tbg ran tbg back w/pin collar and 1° nipple on bottom w/pump out plug. Ran 256 jts 8030° 2-3/8" tbg set @ 8042°. Landed Xmas tree, blew out plug. Released rig @ 12 Midnight.					
	Tested out	2190 MCF after	36 hrs.			SECTIVE .
0	that the information original signed by HN T, HAMPT	n above is true and comple /: ON	te to the best o		d belief.	NOV1 1903 OIL CON. 3 OIL DIST. 3
	Signed Eme	ry C. Arnold	****	ervisor Dist. #	3 .	NOV 1 1965