EMCCG-6 Cutler-1 File-1

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Poo	11	00		F	ormation	_ Masse	erdo		_County_	Rie A	rriba
Ini	tial 🗶		Annu	ual		Spec	cial		Date of	Test_	11-27-59
Com	pany Pacif	ic Ros	threst	Pipel	ine	Lease	29-6		Wel	ll No	37-16
	t										
	ingI										
	•										ess
	ducing Thru										
							Sir	gle-Brade	enhead-G.	G. or	G.O. Dual
Dav	c or comple	OTO11•_		······································	racke			neserve	ort lemb.	 	
		/		.	4		ED DATA				
Test	ted Through				(Meter)	•			Туре Тар)S	
	(Prover)		Flow D		Diff	Temp.	Tubing	Data Temp.	Casing D	ata Term	Duration
No.	(Line)	Cori	fice)		1 1	•	ļ			1	of Flow
SI	Size	S	ize	psig	h _w	°F.	psig	°F.	psig	F.	
1.1		3/4"	10	564		640	610	 	1066	 	81
2.											
3. 4. 5.		,	,			·	l	<u> </u>		 	
5.											
					1	FLOW CAL	CULATION	ıs			
	Coeffici	lent		Pi		Flow	Temp.	Gravity	Compre		Rate of Flow
No.	(24-Hou	ır)	7 h.		psia						Q-MCFPD @ 15.025 psia
1.	12, 365		VW₁	-	576	2060	t	Fg	Fpv		6 1):02) pola
1. 2. 3. 4. 5.					3(9			<u> </u>	1.000		7907
3 e	····										
5.											
					וממ	regimer c	ALCULATI	ONG			
	iquid Hydro ty of Liqui					cf/bbl. deg.					arator Gas
.c		u nyu		1-e ^{-s})		aeg.		Pc- 10	.iic Gravi	P2	wing Fluid
		,		_			•		10		
T	$P_{\mathbf{W}}$		2 _		/ · · · 2		- ,2		-2 -2		2
No.	Pt (psia)	P:	t F	cQ	$(F_cQ)^2$	(F	$\begin{pmatrix} cQ \end{pmatrix}^2 \\ -e^{-s} \end{pmatrix}$	P _w 2	$P_c^2 - P_w^2$		al. Pw
1. 2.	600					<u> </u>		397	775		
3.									117		2-4993
4.										 	
5.					· · · · · · · · · · · · · · · · · · ·						
Abso	lute Potent			Pipel	400 6000	MCFPD;	n_73/1	355			
ADDR	ESS 1	i. Br	a de la composición dela composición de la composición de la composición de la composición dela composición de la composición de la composición dela composición dela composición de la composición dela composición dela composición dela composición dela composición dela composición d	EAPER		·			,		
	T and TITLE ESSED	D. C	Man	- Tre	inction	Inginos					
COMF									COLINY	111	
						REM	ARKS		VELTIA	L	
				, , , , , , , , , , , , , , , , , , ,	\				Nr.	195 ⁹	
					,				OIL CO	W CO	w
	· d	and the second s		a contraction activities	prime to the top to the prime of the prime o			and the second s	/ OIL CL	51.3	//
						4.5			/ V		,

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q T Actual rate of flow at end of flow period at W. H. working pressure (P_w) . MCF/da. @ 15.025 psia and 60° F.
- P_c= 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- Pw Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- hw Differential meter pressure, inches water.
- Fg Gravity correction factor.
- Ft Flowing temperature correction factor.
- Fpv Supercompressability factor.
- n I Slope of back pressure curve.

Note: If $P_{\mathbf{W}}$ cannot be taken because of manner of completion or condition of well, then $P_{\mathbf{W}}$ must be calculated by adding the pressure drop due to friction within the flow string to $P_{\mathbf{+}}$.

ATTES 6	ATION COMMISSION
Jo. Copies	Sissail 6
1966 Tu 850 1966 1966 - 1966 - 1966 1966 1966 1966 1966 1966 1966 1966 1966 1966 1966 1966 1966 1966	MOITUBIES
national section of the section of t	The same of the sa
Place of the part	4
21.08 (2.18) 21.08 (2.18)	
2 G S	