## NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Revised 12-1-55

Pool	Blanco			F	ormation	Mess 1	Ferde	····	_County_	Mo A	rriba	
Init	tialX	x	Annu	al		Spec	ial		Date of	Test	1-16-58	
Comp	oany MCLF	C HORA	enet.	PIPELI		Lease	See Just	29-4	We]	ll No	12-18	
	. <b>B</b> S											
	ing <b>5-1</b> " W											
	ing 2.3/8" W											
	Pay: From_										_	
	lucing Thru:											
	e of Complet						Sin	gle-Brade	enhead-G.	G. or (	G.O. Dual	
	1						ED DATA					
roet	ed Through	( <del></del>		Chalca \	/			kora:	Тъто Тот			
									<u> </u>		<del></del>	
Т	(Prover)	(Cho		Press	Diff.	Temp.	Tubing Press.		Casing I		Duration	
No.	(Line) Size	(Ori	fice) ize	psig	h <sub>w</sub>	$\circ_{\Gamma}$ .	psig	°F.	psig	⊳ <sub>F</sub> .	of Flow Hr.	
SI							1215		1215			
L. 2.		3/4"		78°		60	76	66	<b>20</b> 3		3 Hours	
3 <b>.</b>		1								<del> </del> -		
5.												
<del>-</del> r	Coeffici	ent		р			CULATION		Compre		Rate of Flow	
No .					Factor		Gravity Compress. Rate of Flo Factor Factor Q-MCFPD Fg Fpv @ 15.025 ps		Q-MCFPD			
	12.3650	T) V IW		90 psia		1.000		- rg -9608	1.000		1,069	
} c												
•												
<u>'</u> -					 DDC	regime c	ALCU ATI	OME	<del></del>	<u>.</u>		
<b>T</b>			D-4.	_			WTOO. WIT		<i>6</i> : - 0	÷ C	anakan Oda	
Gas Liquid Hydrocarbon Ratio cf/bbl. Specific Gravity Separator Gas Gravity of Liquid Hydrocarbons deg. Specific Gravity Flowing Fluid									ving Fluid			
			(]	L-e <sup>-5</sup> )				<sup>Р</sup> с— <b>1</b>	,227	_Pc1	505.53	
<del>-</del> T	$P_{\mathbf{w}}$		<del>. T -</del>			1	2	295	2 2	<del></del>		
10.	Pt (psia)	Pt	F	Q	$(F_cQ)^2$	(F)	$\begin{pmatrix} c^{Q} \end{pmatrix}^2 = e^{-s}$	P <sub>w</sub> 2	$P_c^2 - P_w^2$	Ca F	P <sub>w</sub> P <sub>c</sub>	
			#					37.03	1418.9	<u> </u>	1.65	
										1		
										1,		
	lute Potent						n	5/ 1.0446				
DDR	ESS LOS MA	et De	a dame	. No seed	meter.	law Marci	<u> </u>					
II'I'N	T and TITLE ESSED_				THE				<del></del>			
OMP	ANY		<del> </del>	<del></del>		REM	ARKS		<del></del>		1	
									1	الأنسان.	ru /	

## INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

## NOMENCLATURE

- Q I Actual rate of flow at end of flow period at W. H. working pressure ( $P_W$ ). MCF/da. @ 15.025 psia and 600 F.
- $P_c$ = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.
- $P_{w}$  Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- $h_{\mbox{\scriptsize W}}\mbox{\footnotesize I}$  Differential meter pressure, inches water.
- FgI Gravity correction factor.
- $F_t$ : Flowing temperature correction factor.
- $F_{\text{DV}}$  Supercompressability factor.
- n I Slope of back pressure curve.

Note: If  $P_{\mathbf{W}}$  cannot be taken because of manner of completion or condition of well, then  $P_{\mathbf{W}}$  must be calculated by adding the pressure drop due to friction within the flow string to  $P_{\mathbf{t}}$ .

UIL CONSERVATION COMMISSION								
AZTEC DISTRICT OFFICE								
No. Copies Received 3								
DISTRUCTION								
	1 20.00, 1844C							
'perator								
Santa Fs	<i>1</i>							
Promation of fice								
State Land 5775								
J. S. G. S.	J							
Transporter	1 							
File								