Form C-122

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Revised 12-1-55

Poo	ol	Rlane	<u> </u>		F	ormation	He	a Verde		_County_	Rie Ar	riba
Ini	tial_	<u> </u>		Annu	el		Spe	cial		_Date of	Test_5	-17-57
Com	ipany_	Pacifi	e Nor	thwest	Pipeli	ne Corp	Lease	29-	5	Wel	1 No	20-7
Uni	.t	<u> </u>	Sec		p. 2	9 Rg	e 5	Purc	haserU	nconnecte	d	
Cas	ing_	5 1/2	Wt	I	.D	Se	t at	5800 Pe	rf <u>578</u>	8	To 5	276
Tub	ing_	2 3/8	Nt.	I	.D.	Se	t at	7 86 Pe	rf.		То	
												88
										ll Sing		
								Sin	gle-Brade	enhead-G.	G. or 0	3.0. Dual
							OBSER	VED DATA				
163						(Meter)	8 I 7			Type Tap		
	(- P	rover)	(Ch	Flow Da	Press.	Diff.	Temp.		Data Temp.	Casing D		Duration
No.	(-	Mile) Size	407-4-	rice)	ļ	ļ J		1		psig	1	l of Flow
SI			 	· -	1	W		913		1105		SI
1.			3/4"	BM	258		66			842		3 Ers
2.			ļ									
3. 4.			 	· · · · · · · · · · · · · · · · · · ·				 				
5.												
			- 11]	FLOW CAI	LCULATION	S			
		oeffici			Pr	essure	Flow	Temp.	Gravity	Compre	ss.	Rate of Flow
No.	(0) "				Factor			Factor Factor Factor Fpv			Q-MCFPD	
	-	(24-Hou	r)	√ n _w i					rg_			@ 15.025 psia
	14.1	267				300	.994	1	.9608	1.028		4172
2. 3.				 								
4.							······································					
4. 5.												
	ity o	d Hydro f Liqui		rocarbo		PRI	ESSURE (cf/bbldeg.		Speci Speci		tv Flow	rator Gas ving Fluid
No.	$P_{\mathbf{w}}$		P	2 F	Q	(F _c Q) ²	(1	7-0)2	P _w 2	P _c -P _w ²	Ca	1. P _w
		(psia)	- τ			·- U-07	9 3 Q ()	F _c Q) ² L-e ^{-s})	<u> </u>		P	P _C
1. 2. 3.	85	•	<u> </u>	-					729	51.9		2.405
3.												
4.				2.2							1	
5.		i				·				<u>L</u>		
Abso		Potent	ial:	8	3056		_MCFPD	n75/1	1.931			ing Name of Aug
ADDF	RESS_											4 1 2 1 2 1
		TITLE)C	ldene							****
	NESSEI PANY	<i></i>									<u> </u>	
OOII						##	RE	1ARKS			1	STORES OF STREET
			· -								**************************************	September 1

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q I Actual rate of flow at end of flow period at W. H. working pressure ($P_{\rm W}$). MCF/da. @ 15.025 psia and 600 F.
- P_c= 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- P_{w} Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- P_t Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- hw Differential meter pressure, inches water.
- Fg Gravity correction factor.
- F_t Flowing temperature correction factor.
- Fpv Supercompressability factor.
- n I Slope of back pressure curve.

Note: If P_{W} cannot be taken because of manner of completion or condition of well, then P_{W} must be calculated by adding the pressure drop due to friction within the flow string to P_{+} .

OIL CONSERVA	TION COMMI	SSION							
AZIEC DISTRICT OFFICE									
No. Copies Received 3									
DISTRIBUTION									
	10								
Operator	T								
Santa Fe									
Proration Office									
State Land Office	!								
U. S. G. S.	/								
Fransporter									
File									