30-039-07671

STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10.01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Well Operator BURLINGTON RESOURCES OIL & GAS CO. SAN JUAN 29-7 UNIT No. 82 Location of Well: В Twp. 029N 007W RIO ARRIBA Unit Sect 04 Rge. County NAME OF RESERVOIR OR POOL TYPE OF PROD. METHOD OF PROD. PROD. MEDIUM (Oil or Gas) (Tbg. or Csg.) (Flow or Art. Lift) Upper PICTURED CLIFFS Gas Artificial Tubing Completion Lower **MESAVERDE** Artificial Tubing Gas Completion PRE-FLOW SHUT-IN PRESSURE DATA Length of time shut-in Stabilized? (Yes or No) Upper Hour, date shut-in SI press. psig Completion 10/06/2001 120 Hours 149 Lower Completion 10/06/2001 72 Hours 179 FLOW TEST NO. 1 10/09/2001 LOWER Zone producing (Upper or Lower) Commenced at (hour.date)* TIME LAPSED TIME **PRESSURE** PROD. ZONE TEMP REMARKS SINCE* Upper Completion Lower Completion (hour.date) 10/10/2001 96 Hours 149 146 10/11/2001 120 Hours 149 107



Production rate during test

Oil BOPD based on Bbls. in Hours. Grav. GOR

Gas: MCFPD; Tested thru (Orifice or Meter):

MID-TEST SHUT-IN PRESSURE DATA

Upper Hour, date shut-in Length of time shut-in SI press, psig Stabilized? (Yes or No)

Lower Hour, date shut-in Length of time shut-in SI press, psig Stabilized? (Yes or No)

Completion

6968501 358 (Continue on reverse side)

FLOW TEST NO. 2

Commenced at (hour, date)**				Zone producing (Upper or Lower):	
TIME (hour, date)	LAPSED TIME SINCE **	PRESSURE		PROD. ZONE	REMARKS
		Upper Completion	Lower Completion	TEMP.	REMARKS
Production rate du	ring test				
Oil:	B(OPD based on	Bbls. in _	Hours	Grav GOR
Gas:		MCFP	D: Tested thru (Ori	fice or Meter):	
Remarks:		<u></u> .			,,,
					•
Thereby certify tha	nt the information he	rein contained is true	e and complete to the	ne best of my knowledge	:
Approved	116	2001i	9	Operator Burlingto	n Resources
New Mexico O	il Conservation Divi	sion		By Alan &	lon
By GREENA	T SIGNED BY CHA	LIET. PERMIN		Title Operations As	Sociate
l'itle	DEPAIR ON S S	AS INSPECTOR DE	₹ <u></u>	Date Monday, Octo	ber 15, 2001

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within sever days following recompletion and or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tabling have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3 The packer leakage test shall commence when both zones of the dual completion are shart in for pressure stabilization. Both zones shall remain shart in until the well-head pressure in each has stabilized provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note if on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pagencine connection the flow period shall be trace flours.
- 5 . Following completion of Flaw Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 3 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows. 3 hours tests immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desified, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests all pressures throughout the entire test shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 18 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest. New Mexico Packer Leakage Test Form Revised 19-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures egas zones only) and gravity and GOR (oil zones only).