

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office **Santa Fe**
Lease No. **078951**
Unit **Bolin**

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

Notice of Intention to Workover Well

RECEIVED
NOV 19 1962
U. S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO

INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA

November 19, 1962

Well No. **2(OWWO)** located **990** ft. from **S** line and **990** ft. from **W** line of sec. **5**
SW/4 Sec. 5 **29N** **7W** **N.M.P.M.**
Blanco Mesa Verde **Rio Arriba** **New Mexico**

The elevation of the derrick floor above sea level is **6112** ft.

DETAILS OF WORK

State names of casing and tubing, give size, weight, and length of proposed casing, indicate mudding jobs, cementing points, and all other important proposed work.

It is intended to workover this well in the following manner:

A. If Tubing Can Be Pulled:

1. Pull tubing.
2. Clean out to 5270'.
3. Run a full string of 4 1/2" Production casing.
4. Perforate and fracture the Mesa Verde formation.
5. Clean out and run tubing.

B. If Tubing Cannot be Pulled:

1. Cut tubing below 7" shoe.
2. Set 7" cement retainer at approximately 4475' and squeeze open hole.
3. Set whipstock and drill to 5270'.

Understand that this plan requires the approval in writing by the Geological Survey before operations may be commenced.

4. Complete as above.
Company **El Paso Natural Gas Company**

Address **Box 990**
Farmington, New Mexico

By *A. E. McAnally*
Title **Petroleum Engineer**

