


(SUBMIT IN TRIPPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYLand Office **Santa Fe**
Lease No. **078737**
Unit **San Juan 29-5 Unit**CORRECTED

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	PRELIMINARY REPORT OF WATER SHUT OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ALTERING	
NOTICE OF INTENTION TO CUT WATER SHUT OFF	PRELIMINARY REPORT OF ALTERING CASINGS	
NOTICE OF INTENTION TO REPAIR WELL	SUBSEQUENT REPORT OF REPAIRING OR REPAIR	
NOTICE OF INTENTION TO ABANDON WELL	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR	SUPPLEMENTARY WELL HISTORY	

NOTE: ABOVE CHECKED MATTER MUST BE REPORTED TO NOTICE OF INTENTION DATA

March 18, 1963

Well No. 2-3 located 990 ft. from ~~xxxx~~ S. line and 1650 ft. from ~~xxxx~~ W. line of sec. 3

SW/4 Sec. 3 29N 5W N.M.P.M.

Blanco Mesa Verde

Rio Arriba

New Mexico

The elevation of the derrick floor above sea level is 6371 ft.


DETAILS OF WORK

Give names of and expected depths of productive sands; show sizes, weights, and lengths of proposed casings; indicate mud logging jobs, cementing points, and all other important proposed work.

It is intended to plug and abandon this well in the following manner:

1. Spot a 200 sack cement plug across open hole (5194-5745'), pull tubing.
2. Find free point on 7" casing and cut.
3. Spot a 45 sack cement plug across cut-off and pull casing.
4. Spot a 20 sack cement plug in surface and erect a 4' x 4" dry hole marker.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be conducted.

Company **El Paso Natural Gas Company**Address **Box 990****Farmington, New Mexico**By Title **Petroleum Engineer**