

submitted in lieu of Form 3160-5

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

RECEIVED  
BLM

Sundry Notices and Reports on Wells

1. Type of Well  
GAS

2. Name of Operator  
MERIDIAN OIL

3. Address & Phone No. of Operator  
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M  
1040' FSL, 1085' FEL, Sec. 6, T-29-N, R-4-W, NMPM

5. Lease Number  
SF-079756  
6. If Indian, All. or  
Tribe Name  
7. Unit Agreement Name  
San Juan 29-4 Unit  
8. Well Name & Number  
San Juan 29-4 U #11  
9. API Well No.  
30-039-07690  
10. Field and Pool  
East Blanco Pict. Cliffs  
11. County and State  
Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission	Type of Action
<input type="checkbox"/> Notice of Intent	<input checked="" type="checkbox"/> Abandonment
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back
	<input type="checkbox"/> Casing Repair
	<input type="checkbox"/> Altering Casing
	<input type="checkbox"/> Other -
	<input type="checkbox"/> Change of Plans
	<input type="checkbox"/> New Construction
	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Conversion to Injection

13. Describe Proposed or Completed Operations

7-2-96 MIRU. ND WH. NU BOP. TOO H w/144 jts 2 3/8" tbg. TIH w/5 1/2" cmt retainer, set @ 4181'. SDON.

7-3-96 PT tbg to 1000 psi, OK. Circ hole clean w/63 bbl wtr. PT csg, failed. Establish injection into Pictured Cliffs perms. Plug #1: pump 84 sx Class "B" cmt below cmt retainer into Pictured Cliffs perms, pump 69 sx Class "B" cmt above cmt retainer, TOC @ 3588'. TOO H. TIH, perf 3 sqz holes @ 2460'. TOO H. TIH w/cmt retainer, set @ 2416'. Load csg w/wtr. PT csg above cmt retainer, failed. Establish injection. Plug #2: pump 34 sx Class "B" cmt below cmt retainer outside 5 1/2" csg @ 2360-2460'. Pump 13 sx Class "B" cmt above cmt retainer, TOC @ 2304'. TOO H. TIH, perf 3 sqz holes @ 284'. Establish circ down csg & out bradenead w/8 bbl wtr. Plug #3: pump 147 sx Class "B" cmt down csg & out bradenhead. Circ 1 bbl cmt to surface. WOC. SD for holiday.

7-8-96 ND BOP. Cut off WH. Pump 18 sx Class "B" cmt to fill 5 1/2" csg. Install dry hol marker w/10 sx Class "B" cmt. RD. Rig released. Well plugged and abandoned

7-3-96. Approved as to plugging of the well here.  
Liability under bond is retained until  
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Administrator Date 7/17/96

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_

CONDITION OF APPROVAL, if any:

NMOC

P U E D

2 1996