

## NEW MEXICO OIL CONSERVATION COMMISSION

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission District Office within ten days after the work specified is completed. It should be signed and filed as a report on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

|  |          |  |  |
|--|----------|--|--|
| REPORT ON BEGINNING DRILLING OPERATIONS                    |          | REPORT ON REPAIRING WELL                       |  |
| REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL |          | REPORT ON PULLING OR OTHERWISE ALTERING CASING |  |
| REPORT ON RESULT OF TEST OF CASING SHUT-OFF                | <b>X</b> | REPORT ON DEEPENING WELL                       |  |
| REPORT ON RESULT OF PLUGGING OF WELL                       |          |  |  |

October 30, 1932

Aston, N. M.

Date

Place

Following is a report on the work done and the results obtained under the heading noted above at the

Phillips Petroleum Company

Lease Unit 29-6

Well No. 1 in the

NE

Company or Operator

Lease

3

296

64

of Sec. T, R., N. M. P. M.,

Wildcat

Pool

Rio Arriba


County.

The dates of this work were as follows: October 22, 23 and 24, 1932

Notice of intention to do the work was (was not) submitted on Form C-102 on October 30, 1932, and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Spudded in 8:30 AM, October 22, 1932. Drilled to 265' and reamed 13" hole to 15". Ran 6 Jts. 10-3/4" OD 21.69' Armo 34 SJ casing 240.54'. Casing set at 245.14' RKB. Cemented with 200 sack regular idem cement. Pumped plug to 245.14' RKB at 4:51 PM, October 23, 1932. Pressured casing to 900# for 15 min. tested OK. Drilled cement and pressured to 900# for 15 min. Pressure dropped to 400#.



Witnessed by \_\_\_\_\_ Name \_\_\_\_\_ Company \_\_\_\_\_ Title \_\_\_\_\_

APPROVED:  
OIL CONSERVATION COMMISSION

*Henry C. Arnold*  
Name

Title

Nov 3  
Date

1932

I hereby swear or affirm that the information given above is true and correct.

Name

Position

Representing

Address

*C. E. Johnson*  
District Superintendent

Phillips Petroleum Company  
Company or Operator

Box 939, Aston, N.M.