Form 3160-5

## **UNITED STATES**

FORM APPROVED

(June 1990)	DEPARTMEN	T OF THE INTERIOR	;	Expires: March 31, 1993			
,	BUREAU OF L	AND MANAGEMENT	•	5. I	Lease Designation and	d Serial No.	
	SUNDRY NOTICES AN	REPORTS ON WELLS		SF-078410			
Do not us	se this form for proposals to drill	5 to 1 mg	10 / 10	6. lf	f Indian, Allottee or I	Tribe Name	
00,101	• •	PERMIT - " for such propos	<b>A</b> ∨		7.		
		IN TRIPLICATE REC	2000	7. If	f Unit or CA, Agreen	nent Designation	
1. Type of We	ell  X Gas  Well Other	(C) 011 (X)			<u>Júan 29-5 Un</u> Vell Name and No.	it	
2. Name of C	<del>-</del>	land of the second		SJ 2	29-5 Unit #19	)	
Phillips Petroleum Company				9. API Well No.			
3. Address and Telephone No.				30-039-07707			
	ighway 64, NBU 3004, Farmingt of Well (Footage, Sec., T., R., M., or Survey De		05-599-3454	10. 1	Field and Pool, or ex	ploratory Area	
		etipuon)		D3	oo Macayanda		
Unit B, 975' FNL & 1770' FEL Section 6, T29N, R5W			Blanco Mesaverde  11. County or Parish, State				
3600101	11 0, 123N, K3N			1	Arriba,	NM	
	CUECK ADDDODDIATE DOV(	TO INDICATE MATURE	OF NOTICE DEPORT				
12.	CHECK APPROPRIATE BOX(s	TO INDICATE NATURE	OF NOTICE, REPORT,	<u>Jh U</u>	INER DATA_	-	
	TYPE OF SUBMISSION		TYPE OF ACTION				
	Notice of Intent	X Abandonme	nt	닏	Change of Plans		
	X Subsequent Report	Recompletion	n	님	New Construction		
	Subsequent Report	Plugging Ba	ick	님	Non-Routine Frac	turing	
	Final Abandonment Notice	Casing Rep		님	Water Shut-Off		
	That Abandonnion Profes	Altering Ca	sing	H	Conversion to Inje	ection	
		Other		_ LJ (Nc	Dispose Water ote: Report results of mul	Itiple completion on Well	
				Cc	ompletion or Recompletio	n Report and Log form.)	
3. Describe Progive	posed or Completed Operations (Clearly state all e subsurface locations and measured and true vert	pertinent details, and give pertinent dat cal depths for all markers and zones pe	es, including estimated date of starting rtinent to this work.)*	g any pi	roposed work. If wel	l is directionally drill	
	) MIRU A Plus. Killed well w						
	ng. GIH w/5-1/2" CIBP on wir						
PT to 500# - leaked off 200# in 10min. Pumped cement plug #1 w/18# sx Cl B 15.5# cement (4395' - 4295').							
	TOC @ 4245'. PU & layed down 20 jts tubing. RIH w/7-5/8" gauge rig & set 7-5/8" CIBP @ 3816'. Load						
casing w/10 bbls prod. water. PT casing to 500 psi. Leaked off to 200 # in 10 minutes. Pumped #2 plug							
w/91 sx 15.5# Cl B cement from 3816' - 3460'. TOC @ 3410'. PU & layed out 27 jst tubing. Circ. hole							
w/140 bbls inhibited fluid. Pumped #3 plug w/84 sx 15.6#. Cl B cement from 2995' - 2669. TOC @ 2619'.							
PU & layed 24 jt tubing. Opened up well, casing -0- psi. GIH w/tubing & tagged TOC @ 2660'. PT casing to 500 psi for 30 minutes. Good test. PU & layed down @ 35 jts tubin. Pumped #4 plug w/34 sx 15.5# Cl							
B cement (1601' - 1498'). TOC @ 1448'. Ron Snow w/BLM OK'd to GIH to 1420 & pump 150' cement plug							
(1/31/00). Pumped plug #4B w/34 sk 15.6# B cement from 1420' - 1270'. TOC @ 1270'. Perforated 3 holes							
	. Attempted to circ. out Bra						
	radenhead. No Go. Perforate						
	plug #5 (surface) w/105 sx 1						
	ated out bradenhead ND ROP					released	

14. I hereby comply that foregoing is true and correct Signed Use Use Software	Title Sr. Regulatory/Proration Clerk	Date 2/7/00
(This space for Federal or State office use)  Approved by  Conditions of approval, if any:	Title	Date

riq. 1/31/00. Cut off anchors. Well plugged and abandoned.

CCEPTED FOR RECORL

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\* See Instruction on Reverse Side

FR 2000