

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE\*  
(Other instructions on reverse side)Form approved.  
Budget Bureau No. 42 R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 18327

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Conoco 29-4

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

East San Juan - Gallup

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 28, T29N, R4W

12. COUNTY OR PARISH

13. STATE

Rio Arriba

New Mexico

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Continental Oil Company

3. ADDRESS OF OPERATOR

152 North Durbin St., Casper, Wyo. 82601

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

1820' FSL, 970' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether LF, RT, GR, etc.)

7403' CR, 7415' KB

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING


ABANDONMENT\*

Well Progress

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Well spudded 11-16-73. Drilled 15" hole to 515', set 10 3/4" 40.5# casing landed at 512', and cemented with 500 sacks Class "A" cement with 2% CaCl<sub>2</sub> - cement returns to surface. Bumped plug at 9:30 p.m. 11-17-73 with 800 psi.



USGS(6) NMOCC(2) U.S. Forest Service File(2)

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Administrative Supervisor

DATE 12/6/73

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side