

(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPlicate
(Other instructions on re-
verse side)

Form approved
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		5. LEASE DESIGNATION AND SERIAL NO. NM - 4452
2. NAME OF OPERATOR LONE STAR INDUSTRIES, INC.		6. IF INDIAN, ALLOTTEE OR TRIBE NAME -----
3. ADDRESS OF OPERATOR %JOHN E. SCHALK, P. O. BOX 2078, FARMINGTON, N.M.		7. UNIT AGREEMENT NAME -----
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 2456' FROM THE NORTH LINE, 795' FROM THE EAST LINE SECTION 24, TOWNSHIP 29 NORTH, RANGE 5 WEST		8. FARM OR LEASE NAME SCHALK 52
14. PERMIT NO.		9. WELL NO. 6
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6531' GR		10. FIELD AND POOL, OR WILDCAT BLANCO MESA VERDE
		11. SEC. T., R., M., OR BLK. AND SURVEY OR AREA SEC. 24, T-29N, R-5W
		12. COUNTY OR PARISH RIO ARriba
		13. STATE NEW MEXICO

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

WELL HISTORY

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*


SCHALK 52 WELL NO. 6

SPUDDED AT 8:45 PM ON 6-14-74

6-15-74

TD - 350'

RAN 8 JOINTS OF 8-5/8", 32# KS CASING. TOTALING 334.40'. SET AT 347.40'. CEMENTED WITH 300 SACKS OF CLASS "B" CEMENT WITH 3% CALCIUM CHLORIDE AND 1/4# FLOWSEAL PER SACK. CEMENT CIRCULATED. CEMENT FELL 7' AND THEN STOPPED. PLUG DOWN AT 3:15 PM ON 6-15-74.



18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

AGENT

DATE

6-28-74

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side