Submit 3 Conies

State of New Mexico

to Appropriate District Office	propriate Energy, Minerals and Natural Resources Departmen		t Revised 1-1-6		
DISTRICT I P.O. Box 1980, Hobbs NM 88241-1980 DISTRICT II P.O. Drawer DD, Artesia, NM 88210 DISTRICT III	OIL CONSERVATION 2040 Pacheco St Santa Fig. 10 [2]		WELL API NO. 30-039-21416 5. Indicate Type of Lease STATE	FEE X	
1000 Rio Brazos Rd., Aztec, NM 87410		2 1889 B	6. State Oil & Gas Lease No.		
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR REPART" (FORM C-101) FOR SUCH PROPOSALS.)			7. Lease Name or Unit Agreement Name		
1. Type of Well: OIL GAS WELL WELL WELL X	OTHER	017654	San Juan 29-6 Unit 0	09257	
2. Name of Operator Phillips Petroleum Company			8. Well No. SJ 29-6 Unit #54A		
3. Address of Operator 5525 Highway 64, NBU 3004,	Farmington NM 87401		9. Pool name or Wildcat Blanco Mesaverde 72	2319	
4. Well Location Unit Letter E : 148	BO Feet From The North	Line and80	0 Feet From The West	Line	
Section 4	Township 29N Range		NMPM Rio Arriba	County	

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data							
NOTICE OF INTENTION TO:			SUBSEQUENT REPORT OF:				
PERFORM REMEDIAL WORK		PLUG AND ABANDON		REMEDIAL WORK	ALTERING CASING		
TEMPORARILY ABANDON		CHANGE PLANS		COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT		
PULL OR ALTER CASING				CASING TEST AND CEMENT JOE	3		
OTHER: Add pay & stimul	ate		_ [X]	OTHER:			

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

 ${\tt MIRU.} \quad {\tt ND WH \& NU BOPs.} \quad {\tt POOH w/production \ tubing.} \quad {\tt Isolate \ existing \ Mesaverde \ perfs \ with \ bridge \ plug.}$ PT casing. If casing fails test - isolate failure. Remediate with cement.

If well records indicate no cement across the Lewis Shale interval, it may be necessary to run a casing bond log (CBL). Shoot squeeze holes in casing and pump sufficent volumes of cement to cover and isolate the Lewis Shale.

Perforate and stimulate the Lewis Shale (perfs to be determined after logs are run). Retrieve bridge plug and run production tubing. Flow test the Lewis Shale.

A workover nit may be required

ORIGINAL SIGNED BY FRNIE SUSCI

A MOTROVET PTE)				
I hereby certify that the informa	ition above is true and complete to the best of my kn	owledge and bel	lief.		
SIGNATURE //COL	y Classif	TITLE	Regulatory Assistant	DATE	6-18-98
TYPE OR PRINT NAME	Patsy Clugston			TELEPHONE NO.	505-599-3454

(This space for State Use)

APPROVED BY ..

DEPUTY OIL & GAS INSPECTOR, DIST AS	JUN	2	3	1998
-------------------------------------	-----	---	---	------