Form 9-331 (May 1963)

16.

RS

UNITED STATES SUBMIT IN TRIPLICATE* Other instructions on reverse side)

Budger Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO. NM 01'2698

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Rio Arriba

N.M.

GEOLOGICAL SURVEY

CHAIDDY	NOTICES	ANID	DEDODIC	ON	WELLC
SUINDKY	INCHICE2	AND	REPURIS	ON	WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals.) 1. 7. UNIT AGREEMENT NAME OIL WE'L GAS WELL San Juan 29-6 Unit OTHER NAME OF OPERATOR 8. FARM OR LEASE NAME Northwest Pipeline Corporation San Juan 29-6 Unit ADDRESS OF OPERATOR 9. WELL NO. P.O. Box 90 - Farmington, New Mexico 23A LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)

At surface 1790 FNL & 885 FWI. 10. FIELD AND POOL, OR WILDCAT Blanco Mesa Verde 11. SEC., T., R., M., OR ELK. AND SURVEY OR ARE \ Sec. 12, T29N, R6W 14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 12. COUNTY OR PARISH | 13. STATE 6506' GR

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:				SUBSEQUENT REPORT OF:		
TEST WATER SHUT-OFF		PULL OR ALTER CASING		WATER SHUT-OFF	REPAIRING WELL	
FRACTURE TREAT		MULTIPLE COMPLETE		FRACTURE TREATMENT	ALTERING CASING	
SHOOT OR ACIDIZE		ABANDON*		SHOOTING OR ACIDIZING	ABANDONMENT*	i
REPAIR WELL		CHANGE PLANS		(Other) spud & surface		X
(Other)				(Note: Report results of multipl Completion or Recompletion Repo	le completion on Well ort and Log form.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated d. e of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Spud 12 1/4" hole. Drilled to 192'. Ran 9 5/8" casing set 8-4-77 at 192' KB. Cemented with 125 sks. Class "B" with 1/4% gel flake per sack and 3% CC. Tested surface casing to 600 PSI.



-						
18	SIGNED .P. Slattery	TITLE	Drilling Engineer	DATE 8/10/77		
	(This space for Federal or State office use)			,		
/ch	APPROVED BYCONDITIONS OF APPROVAL, IF ANY:	TITLE		DATE		