

**UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY**

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF 079756-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

San Juan Unit 29-4

8. FARM OR LEASE NAME

21

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT
Blanco Mesaverde Extension & East Blanco Pictured Cliffs

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

**NW/4 SW/4 Section 5,
T-29-N, R-4-W**

12. COUNTY OR PARISH

Rio Arriba

13. STATE

NM

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

AMOCO PRODUCTION COMPANY

3. ADDRESS OF OPERATOR

501 Airport Drive Farmington, NM 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)
At surface

1785' FSL x 1785' FWL, Section 5, T-29-N, R-4-W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

7491' GL, 7503' KB

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☒

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☒

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Completion operations commenced 11/16/77. Tripped in hole and drilled cement on top of liner @ 4484, cleaned out to PBD of 6704: Pressure tested casing to 3000 psi; held 15 minutes OK. Perforated 6308-12, 6338-48, 6367-73, 6388-04, 6418-22, 6442-50, 6466-70, 6489-93, 6498-6504, 6526-42, 6562-6604, and 6660-76 with 1 SPV. Sand-water fraced in 2 stages with 175,200 lbs. sand and 87,600 gallons frac fluid. Tripped in hole with tubing and cleaned out sand 6630 to 6704. Landed tubing at 6666; flowed to clean up. Tested 12/20/77 190 MCWD. Will attempt to dually complete well in the Pictured Cliffs formation by setting a retrievable bridge plug at 4460 and perforate 4208-50, 4278-4318, 4362-78, 4396-4438 with 1 SPV and foam frac with 200,000 gallons and 400,000 lbs. sand.



18. I hereby certify that the foregoing is true and correct

SIGNED

[Signature]

TITLE **Area Adm. Supervisor**

DATE **1/16/78**

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

RECEIVED

JAN 17 1978

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY
FPM-10, 6610.

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.