1.77.69

A. 18

## UNITED STATES

UNITED STATES	5. LEASE SF 080179
DEPARTMENT OF THE INTERIOR  GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME San Juan 29-5 Unit 8. FARM OR LEASE NAME
1. oil gas well other	San Juan 29-5 Unit 9. WELL NO.
<ol> <li>NAME OF OPERATOR         Northwest Pipeline Corporation</li> <li>ADDRESS OF OPERATOR         P.O. Box 90, Farmington, N.M. 87401</li> <li>LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)         AT SURFACE: 1010' FNL &amp; 930' FEL         AT TOP PROD. INTERVAL: Same as above         AT TOTAL DEPTH: Same as above</li> <li>CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA</li> </ol>	#102  10. FIELD OR WILDCAT NAME  Undesignated Pictured Cliffs  11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  Sec 9 T29N R5W  12. COUNTY OR PARISH Rio Arriba New Mexico  14. API NO. 30-039-22468  15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO:  SUISEQUENT REPORT OF:  TEST WATER SHUT-OFF  FRACTURE TREAT  SHOOT OR ACIDIZE  REPAIR WELL  PULL OR ALTER CASING  MULTIPLE COMPLETE  CHANGE ZONES  ABANDON*  (other)  Drlg operations  X  U. S. GECLOGIC  FARMINGTOR  ABANDON*  (other)  Drlg operations  TO DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine  2-14-81 to 2-20-81  Drlg ahead to a depth of	(NOTE: Report results of multiple completion of zone chalge on Form 9–30.)  AL SURVEY  AL SURVEY  AL SURVEY  A SURVE
2-21-81 TD'ed w/ bit @ 4010'. GO ran IEL 2-22-81 Ran 132 jts (3992') of 2-7/8", 6.4 Buttress) & set at 4005' KB. Float @ 39 65/35 poz w/ 12% gel & 12-1/2# gils/sx. 12-1/2# gils/sx. Plug displaced w/ 1 bb down @ 1335 hrs. Pressure plug to 400# temp survey & found top of cmt @ 2500' w hrs.	#, J-55 (44' of 8 RD & 3948' of 97'. HOWCO cemented w/ 85 sx Cl "B" Tailed w/ 100 sx CL "B" w/ 6% gel & 1 of acetic acid & 22 bbls of wtr & 5 ST w/ 250# on csg. Wilson ran
NOW WAITING ON COMPLETION.	_
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
Sidile Hrace	Clerk DATE Feb 23, 1981
ACCEPTED FUIL REGULD  APPROVED BY CONDITIONS OF APPROVAL IF ANY: FEB 2 6 1981  NIMOCC	DATE
EARMINGTON DISTRICT  See Instructions on Rever	rse Sid€