Form 3160-5 (June 1990)

Date: 7/13/90

## UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM	APPR	ov	ED	
Budget Bun	eau No.	10	04-01	3:
Expires:	March	11	1003	

		Expires:	M	arch	31, 199	<b>)</b> 3
5.	Lease	Designat	ion	and	Serial	No.
		8426-				

	1	SF-0/84
REPORTS ON WELLS		,-
INTERCOMIS ON MELLS		

SUNDRY NOTICES AND Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. 6. If Indian, Allottee or Tribe Name Use "APPLICATION FOR PERMIT—" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE ee計構造了0 a.1 F a 15 San Juan 29-6 Unit 1. Type of Well Oil Well Gas Well Other 8. Well Name and No. 2. Name of Operator 211 PHILLIPS PETROLEUM COMPANY 9. API Well No. 3. Address and Telephone No. 30-039-24723 300 West Arrington Suite 200, Farmington, NM 87401 505/599-3400 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Basin Fruitland Coal 11. County or Parish, State Unit H 2030' FNL & 1145' FEL 520, T29N, RGW Rio Arriba CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Change of Plans Recompletion **New Construction** Plugging Back Non-Routine Fracturing 1 1990 Casing Repair Water Shut-Off Altering Casing Conversion to Injection Other As Per NTL-FRA-90-1 Dispose Water (Note: Report results of multiple completion on Well

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Time Started:

Description of cement job to fulfill requirements for protection of usable water zones including the Ojo Alamo Formation, as per NTL-FRA-90-1.

Hole Size 8-3/4 Casing Size 7." 23# J-55 New	_ rime combieted:	1453	
	Casing Seat	3033	Ft
Turbo Centralizers at 2520 , 2477 , 2432 .		1 1 Add	
Spring Type Centralizers at 3012 , 2947 , 2857		2700	
Mud Flush 10 BBls, Spacer 10 Fresh Water.		2700	
Lead Slurry 500 sx 65/35 POZ, 12% Gel, 1/4#/sx Flocele, 11.	7 ppg @ 2.30 ft <sup>3</sup> /	sx yield.	
Mid Slurry 100 sx Standard, 1/4#/sx Flocele, 15.6 ppg @ 1.	18 ft <sup>3</sup> /sx yield.		
Tail Slurry 50 sx Standard, .75% CFR-2, 15.6 ppg @ 1.06 ft3	/sx yield.		
Displaced Plug with Bbls Fresh Water.	,		
Volume Cement Circulated 76 Bbls/Sacks Average Pressure 594 PSI, Average Rate 5 BPM	Bumped Plug with	1400	DCT

14. I hereby certify that the foregoing is true and correct R. A. Allred Title Drilling Supervisor (This space for Federal or State office use) 

**FARMINGTON RESOURCE AREA** 

Time Completed:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction