NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Revised 12-1-55

Pool	Blan	00				Fc	rmation	nMes	a Verde	~~	County_	Rio	Arribe	
Initi	al	XX									Date of			
Compa	ny PA	CIFI	C NOR	THVI	st :	PIPELI		Lease	San Ju	n 29-6	We	ll No	57	'-33
Unit	A	s	Sec	33	_Twp	29	R R	ge 6w	Pur	chaser	not come	eted		
											50421			
Tubin	g 1-1/	4" W	't	2.3	_I.	D	Se	et at	634' _P	erf		_To		
Gas Pa	ay: F	rom_		To) <u></u>		L	x	G65	o		_Bar.Pr	ess	12
Produ	cing I	'hru:	Ca	sing	3 <u></u> _		Tu	ibing	x x	Type W	ellel	ngle		
Date o	of Con	plet	ion:_				Packe	r	Si	ngle-Brad Reserv	enhead-G. oir Temp.	G. or	G.O. I	oual
Teste				Flow	ı Da	ta	(Helet)			g Data	Type Tap)ata		
No.	(Prov (Lin		(Ch (Ori			Press.	Diff.	•	Press	. Temp.	Press.	Temp.	7	Duration of Flow
	Siz	-		ize	' 1	psig	hw	°F•	psig		psig	°F∙		Hr.
SI l.			3/	4	-+	150		470	108 15		1096	 	+	hours
2 . 3.	· · · · · · · · · · · · · · · · · · ·				二				<u>-</u>					
4.					\pm					<u> </u>		 		
5.					\Box						L			
								FLOW CAL						
No.	Coefficient (24-Hour)			$\sqrt{h_{\mathbf{w}}p_{\mathbf{f}}}$		- l	essure osia	Flow Temp. Factor Ft		Factor	Compress. Factor F _{pv}		Rate of Flow Q-MCFPD @ 15.025 psia	
1.	12.3650		V			52	1.0127		F _g	1.017		1982		
2 . 3.														
4. 5.														
	uid H				rboi			cf/bbl.deg.	ALCU AT:	Spec: Spec:	ific Gravi ific Gravi 1108	ty Flo	wing F	
No.	w t (ps	ia)	P:	2 t	Fc		$(F_cQ)^2$	(F ₀	2Q) ² -e-s)	038 _{Pw} 2	P _c ² -P _w ²		al.	Pw Pc
2. 3.		-		$-\Gamma$		$ \Box$			$ \top$	1077.4	150.3			8.17
3.														
5.												†		
ADDRES AGENT	Y PACI S 41 and T	FIC W	MORIE		WAY	Farm	CORPOR Ington, Well To	MCFPD; ATION New Nex	160	.75/ 4.8	323			
VITNES COMPAN														
								REM/	ARKS	San	APR3 195 L CON. C LIGT. 3	8 om.)		

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q \equiv Actual rate of flow at end of flow period at W. H. working pressure (P_W). MCF/da. @ 15.025 psia and 60° F.
- P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- Pw Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt- Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- $h_{\ensuremath{\mathbf{w}}^{-}}$ Differential meter pressure, inches water.
- $F_g \subseteq Gravity$ correction factor.
- F_{t} Flowing temperature correction factor.
- Fpv Supercompressability factor.
- n I Slope of back pressure curve.

Note: If $P_{\rm W}$ cannot be taken because of manner of completion or condition of well, then $P_{\rm W}$ must be calculated by adding the pressure drop due to friction within the flow string to $P_{\rm t}$.

	FOR CONTRACT	CE
	7 * 5 \$	Communication of the Communica
e de la companya del companya de la companya del companya de la co		
	: /	
· Prince		
	· · · · · · · · · · · · · · · · · · ·	1
1000-00000		
/ 77) y	1	1