Form 31605 (November 1983) (Formerly 9-331)	UNITED STATES DEPARTMENT OF THE INTERIOR	SUBMIT IN TRIPLICATE (Other instructions on re	Form approved.  Budget Bureau-No. 1004-0135  Expires August 31, 1985  5. LEASE DESIGNATION AND SERIAL NO.		
SUN	BUREAU OF LAND MANAGEMENT  IDRY NOTICES AND REPORTS  form for proposals to drill or to deepen or plans had use "APPLICATION FOR PERMIT—" for each per	N WELLS ck to a different reservoir.	NM-10431	E OR TRIBE NAME	
OIL GAS X OTHER			7. UNIT AGREEMENT NAME		
2. NAME OF OPERATOR			8. FARM OR LEASE NAM	8. FARM OR LEASE NAME	
FALCON SEABOARD GAS COMPANY 3. ADDRESS OF OPERATOR			29-4 Carson	29-4 Carson 12	
			9. WELL NO.	9. WELL NO.	
c/o Dave Simmons P. O. Box 48 Farmington, NM 87499  1. Location of Well (Report location clearly and in accordance with any State requirements.*  See also space 17 below.)			1 10. FIELD AND POOL, OR WILDCAT		
At surface 1770' FNL & 960' FEL			Basin Fruitland Coal 11. SEC., T., E., M., OR BLK. AND SURVEY OR AREA		
			Sec 12, T29N		
14. PERMIT NO.	15. ELEVATIONS (Show where	+1 01 01;	12. COUNTY OR PARISH	13. STATE	
	7112 <b>'</b> GR		Rio Arriba	NM	
16.	Other Data	· .			
TEST WATER SHUT-	FF PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING V	FELL	
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CA	ASING	
SHOOT OR ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING	ABANDONMEI		
REPAIR WELL	CHANGE PLANS	(Other) Spud, surf	ace casing a cer		
(Other)		Completion or Recom	pletion Report and Log for	rm.)	
proposed work. If nent to this work.)		eas and measured and true verti	s, including estimated dat cal depths for all markers	e of starting any s and zones pert!	
July 12, 1	Spud well at 7:00 PM. Dri Ran 7 joints 8-5/8" 24# k Landed casing with bottom Cemented with 175 sacks ( 1/4#/sk. flocele. Circula	Arapahoe Rig # 7 moved on location.  Spud well at 7:00 PM. Drilled 12-1/4" hole to 275'  Ran 7 joints 8-5/8" 24# K55, ST&C R3 casing (251.02')  Landed casing with bottom at 264' KB.  Cemented with 175 sacks (207 cu. ft.) Class "B" w/ 2% CaCl2 and 1/4#/sk. flocele. Circulated 15 bbls cement to surface.  Plug down at 5:15 AM 7-13-90. WOC.			
July 13, 1	990 WOC 12 hours. Install BOR to 800 psig. for 30 minut		face casing and	ВОР	
		JUL31 OIL CON	I. DIV.		

Agent DATE 7-15-90

(This space for Federal or State office use:

APPROVED BY
CONDITIONS OF APPROVAL. IF ANY:

NMOCD

Agent

Agent

Agent

DATE 7-15-90

ACCEPTED FOR RECORD

DATE

JUL 24 1990

FARMINGTON RESOURCE AREA

There ends to the terminal of the same of the control of the contr

BY 2111