Form 3160-5 (June 1990)

300 West Arrington Suite 200, Farmington, № 87401 505/599-3400

10. Field and Pool, or Exploratory Area Basin Fruitland Coal

| Form 3160-5 (June 1990) | DEPARTMENT OF THE INTERIOR | Budget Bureau No. 1004-0135 Expires: March 31, 1993 | | |
|--|--|--|--|--|
| | BUREAU OF LAND MANAGEMENT | 5. Lease Designation and Serial No. SF-080379 | | |
| Do not use this | SUNDRY NOTICES AND REPORTS ON WELLS form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals | 6. If Indian, Allottee or Tribe Name | | |
| | SUBMIT IN TRIPLICATE | 7. If Unit or CA, Agreement Designation San Juan 29-6 Unit | | |
| 1. Type of Well Oil Well Well W | as Other | 8. Well Name and No. 204 | | |
| 2. Name of Operator PHILLIPS P 3. Address and Telepho | PETROLEUM COMPANY ne No. | 9. API Well No. 30-039-24822 | | |

| 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) | | | | |
|--|---|---|--|--|
| FNL & 1272' FEL | Set, T29N, RGW | 11. County or Parish, State Rio Arriba, NM | | |
| APPROPRIATE BOX(s) TO | INDICATE NATURE OF NOTICE, REF | PORT, OR OTHER DATA | | |
| SUBMISSION | TYPE OF ACTION | | | |
| Intent | Abandonment Recompletion Plugging Back | Change of Plans New Construction Non-Routine Fracturing | | |
| andonment Notice | Casing Repair Altering Casing Other As Per NTL-FRA-90- | Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well | | |
| 3 | FNL & 1272 FEL APPROPRIATE BOX(s) TO SUBMISSION Intent Int Report | FNL & 1272' FEL APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REI BUBMISSION TYPE OF ACTI Abandonment Recompletion Plugging Back Casing Repair Altering Casing | | |

Description of cement job to fulfill requirements for protection of usable water zones including the Ojo Alamo Formation, as per NTL-FRA-90-1.

| Date: 7/24/90. | Time Started | : 0935 | | Time Completed: | 1037 | |
|---|----------------------|--------------------------------|--------------|------------------------------------|--------|-----|
| Hole Size 8-3/4 | | | | Casing Seat | 3460 | Ft. |
| Turbo Centralizers at Spring Type Centralize | 2863,2 | 782 , 27: | 20 | , 3202 , | 3123 | |
| Mud Flush 10 B | Bls, Spacer | 10 Fresh | n Water. | | | |
| Lead Slurry 500 sx 65 | | | | | | |
| Mid Slurry 100 sx St | andard Ideal, | 1/4#/sx Floce | le, 15.6 ppc | @ 1.18 ft ³ /sx y | yield. | |
| Tail Slurry50 sx St | andard Ideal, | .75% CFR-3, 1 | 7.5 ppq @ .9 | $94 \text{ ft}^3/\text{sx yield.}$ | | |
| Displaced Plug with | 133 Bbls | Fresh Water. | | | | |
| Volume Cement Circulat Average Pressure72 | ed 10 8 PSI, Aver | Bbls/ Sæcks age Rate | 5 BPM, I | Bumped Plug with | 1800P | sı. |

| | R. A. Allred Fide Drilling Supervisor | Detc 9-14-90 |
|---|---------------------------------------|---------------------|
| (This space for Federal or Proffi See 0 5 | ide | ACCEPTED FOR RECORD |
| Approved by Conditions of approval, if | | SEP 26 1990 |

rime because the property and willfully to make to any department or agency of the United ARMINETONERECTIONS of Manualest statements Title 18 U.S.C. Section 1001, makes or representations as to any matter title is