FORM APPROVED Form 3160-5 UNITED STATES Budget Bureau No. 1004-0135 DEPARTMENT OF THE INTERIOR (June 1990) Expires: March 31, 1993 **BUREAU OF LAND MANAGEMENT** 5. Lease Designation and Serial No. SF-080377 SUNDRY NOTICES AND REPORTS ON WELL'S 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. \subseteq Use "APPLICATION FOR PERMIT - " for such proposals ت 7. If Unit or GA, Agreement Designation SUBMIT IN TRIPLICATE San Juan 29-6 Unit 1. Type of Well 8. Well Name and No. X Gas Well 2. Name of Operator - #257R Phillips Petroleum Company 9. API Well No. 3. Address and Telephone No. 30-039-25456 505-599-3454 5525 Highway 64, NBU 3004, Farmington, NM 87401 10. Field and Pool, or exploratory Area 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Basin Fruitland Coal Unit D, 1312' FNL & 937' FWL Section 9, T-29-N, R-6-W 11. County or Parish, State NM Rio Arriba, CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF ACTION TYPE OF SUBMISSION Change of Plans Abandonment **New Construction** Recompletion Non-Routine Fracturing Plugging Back Water Shut-Off Casing Repair Final Abandons Conversion to Injection Altering Casing 7" casing Dispose Water Other : Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 11-8-94 RIH w/8-3/4" bit & drilled through cement to TD @ 3155'. RIH w/7" 23#, K-55 casing. Set casing @ 3153' (KB). PT. RU Western & pumped 10 bbls flush & 20 bbls H20 followed by 500 sxs Cl B cement w/12% gel with 1/4#/sx cellophane flake, (yield 2.11 ft3/sx mixed @ 12 - 12.2 ppg w/11.28 gal/sx water) total 1038 ft3 lead & tail in w/150 sxs Class B w/2% CaCl2 with 1/4#/sx Cellophane flake (yield 1.18 ft3/sx mixed @ 15.6 - 16 ppg w/5.2 gal/sx wtr total 174 ft3) total 1212 ft3 cement slurries. Displaced with 123 bbls water. Bumped plug to 1900 psic Check float (OK). Plug down @ 1245 11 11 04 Circulated 50 bbls (150 sys 227 ft)

1900 psi. Check float (OK). Plug down @ 1345 11-11-94. Circulated 60 bbls (160 sxs- 337 ft lead slurry to surface. Total cement in wellbore annulus => 865 ft3. ND BOP. Set 7" csg slips w/55-60,000#. Release rig @ 1600 hrs 11-11-94. Waiting on air equipment.

I hereby certify that the foregoing is true and correct Signed	Title Environmenta	1/Regulatory Eng.	Date 11-15-94
This space for Federal or State office use)			
Approved by	Title		r UR RECURS
Conditions of approval, if any:		سلطا مسال	FUR MEDICAL

or representations as to any matter within its jurisdiction.