STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

## OIL CONSERVATION DIVISION

Page 1 Revised 10 01 78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

## NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Well 93A SAN JUAN 29-7 UNIT No. BURLINGTON RESOURCES OIL & GAS CO. Lease Operator Location **RIO ARRIBA** County 029N Rge. 007W 02 Twp. С of Well: Unit Sect PROD. MEDIUM METHOD OF PROD. TYPE OF PROD. NAME OF RESERVOIR OR POOL (Tbg. or Csg.) (Flow or Art. Lift) (Oil or Gas) Upper Artificial Tubing PICTURED CLIFFS Gas Completion Lower Artificial Tubing Gas **MESAVERDE** Completion PRE-FLOW SHUT-IN PRESSURE DATA Stabilized? (Yes or No) SI press, psig Length of time shut-in Hour, date shut-in Upper 182 Completion 120 Hours 10/26/2001 Lower 185 72 Hours Completion 10/26/2001 FLOW TEST NO. 1 LOWER 10/29/2001 Zone producing (Upper or Lower) Commenced at (hour.date)\* PRESSURE PROD. ZONE TIME LAPSED TIME REMARKS TEMP Lower Completion SINCE\* Upper Completion (hour.date) Turned on MV. 182 157 10/30/2001 96 Hours 140 182 10/31/2001 120 Hours

Production rate during test

Oil BOPD based on Bbls. in Hours. Grav. GOR

Gas: MCFPD: Tested thru (Orifice or Meter):

MID-TEST SHUT-IN PRESSURE DATA

Upper Hour, date shut-in Length of time shut-in SI press, psig Stabilized? (Yes or No) Completion

Lower Hour, date shut-in Length of time shut-in SI press, psig Stabilized? (Yes or No) Completion

3435032 346 (Continue on reverse side)

## FLOW TEST NO. 2

TIME LAPSED TIME PRESSURE  (hour, date) SINCE "Upper Completion Lower Completic				Zone producing (Upper or Lower):		
		PRES	SSURE	PROD. ZONE	DEMANUS	
(,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	SINCE	Upper Completion	Lower Completion	n TEMP.	REMARKS	
<del>,</del>						
Production rate du	ring test					
Oil:	BC	PD based on	Bbls. in	Hours	GravGOR	
haraby partific that	1 th x in farmant 1			<del></del>		
nereoy certify that	NUV 2 20	ontained is true	and complete to t	the best of my knowledg	e.	
Approved		19		OperatorBurlingt		
	l Conservation Divis			01	0.	
<b>MAN</b>	A CHANG	ST. PSINNES		By Alexo	Lay:	
By	·			Title <u>Operations A</u>	ssociate	
itle	4 965 199 201	NF A	·	Date Thursday, No	vember 01, 2001	

## NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- I. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2 At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4 For Flow Test No , one zone of the dual completion shall be produced at the normal rate of production while he other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note, if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- 5 . Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above
- 6 Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows. 3 hours tests immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-dax tests immediately prior to the beginning of each flow period at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests all pressures throughout the entire test shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8 The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only)