

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

RECEIVED  
BLM

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir  
Use "APPLICATION FOR PERMIT - " for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Phillips Petroleum Company

3. Address and Telephone No.

5525 Highway 64, NBU 3004, Farmington, NM 87401

505-599-3454

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit A, 907' FNL & 1253' FEL  
Section 27, T-29-N, R-6-W

5. Lease Designation and Serial No.

SF-080377

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

San Juan 29-6 Unit

8. Well Name and No.

SJ 29-6 #264

9. API Well No.

30-039-25535

10. Field and Pool, or exploratory Area

Basin Fruitland Coal

11. County or Parish, State

Rio Arriba NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other Spud report  
☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

7-16-95

MIRU Big A #23. Spudded 9-7/8" hole at 0300 hrs. 7-17-95. Drilled to 295'. Ran 7-5/8" 26.4# J-55 STC casing and set @ 291'. Pumped 10 bbls H2O ahead. Dowell mixed and pumped 150 sx (31 bbls) Class G cement with 3% CaCl2, 1/4#/sx celloseal, & displaced with 13.5 bbls H2O, cir. 87 sx (18 bbls) cement to surface. Good circ. Plug down 1535 hrs. WOC, NU & test BOPs. Good test.

RECEIVED  
JUL 21 1995  
OIL & GAS DIV.  
DIST. 8

14. I hereby certify that the foregoing is true and correct

Signed

*E. H. Haseley*

Title

Envir./Regulatory Engineer

Date

7-25-95

(This space for Federal or State office use)

Approved by

Title

ACCEPTED FOR RECORD

Conditions of approval, if any:

JUL 28 1995

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\* See Instruction on Reverse Side

FARMINGTON DISTRICT OFFICE  
*E. H. Haseley*