Form 3160-5 (August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

SUNDRY NOTICES AND REPORTS ON WELLS

FORM APPROVED
OMB NO. 1004-0135
expires: November 30, 200

5. Lease Serial No.

 000170	

SF.	-080179
6.	If Indian, Allottee or Tribe Name

SUBMIT IN TRIPLICATE - Other instructions on reverse side	
	7. If Unit or CA/Agreement, Name and/or No.
1. Type of Well Oil Well X Gas Well Other	San Juan 29-5 Unit San Juan 29-5 Unit Well Name and No.
2. Name of Operator Phillips Petroleum Company	SJ 29-5 Unit #49A 9. API Well No.
3a. Address 3b. Phone No. (include 5525 Highway 64, NBU 3004, Farmington, NM 87401 505-599-3454	area code) 30 - 039 - 26542 10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Unit F, 1850' FNL & 1450' FWL Section 9, T29N, R5W	Blanco Mesaverde 11. County or Parish, State Rio Arriba, NM
12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF	NOTICE, REPORT, OR OTHER DATA
TYPE OF SUBMISSION T	TYPE OF ACTION
Notice of Intent Acidize Deepen Alter Casing Fracture Treat	Production (Start/Resume) Water Shut-Off Reclamation Well Integrity
X Subsequent Report Casing Repair New Construction	
Final Abandonment Notice Change Plans Plug and Abando Convert to Injection Plug Back	n Temporarily Abandon 7" casing report Water Disposal
following completion of the involved operations. If the operation results in a multiple completion of testing has been completed. Final Abandonment Notices shall be filed only after all requirements, determined that the final site is ready for final inspection.) RiH w/8-3/4" bit & tagged cement @ 310'. Drilled cement & shoe hole. RIH w/7", 20#, J-55 casing and set @ 3955'. RU BJ to cem clean, 10 bbls dye water. Ahead of 520 sx (1237 cf - 220 bbl sl 0.25#/sx Cello-flake, 5#/sx Gilsonite, 10#/sx CSE, 3% KCL, 0.4%	to 350'. Drilled ahead to 3955'. Circ. ment. Pumped 10 bbls H2O, 10 bbls mud urry) Type 3, 35:65 POZ, 6% Bentonite,
Then tail - 50 sx (70 cf - 12.46 bbls slurry) Type 3, 1% CaCl2, bbls H20. Lost returns at tail end of displacement. Had trace hrs 1/13/00. ND BOP & set slips and cut off casing. NU BOP sta 3000 psi. PT casing and rams to 200 psi low and 1500 psi high.	0.25#/sx Cello-flake. Displaced w/158 of cement to surface. Plug down @ 13:33 ake & manifold. PT BOP - 200 psi then
	27
14. I hereby certify that the foregoing is true and correct Name (Printed Typed) Patsy Clugston Sr	. Regulatory/Proration Clerk
	2/01 ACCEPTED FOR RECOF
THIS SPACE FOR FEDERAL OR STATE	OFFICE USE
Approved by Title	Dale EB 0 7 ZUUI
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease	FARMINGTON FIED OFFICE

Title 18 U.S.C. Section 1001, and Title 43 U.S.C. Section 1212, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.