Form 3160-5 (August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB NO. 1004-0135 Expires: November 30, 2000

5. Lease Serial No.

SUNDRY NOTICES AND REPORTS ON V	WELLS	NM-03188
Do not use this form for proposals to will or to re-en	er an	6. If Indian, Allottee or Tribe Name
abandoned well. Use Forta 360-3 (APD) ton Such pro	poe and	
SUBMIT IN TRIPLICATE Other In Cuctions of le	œ <u>//// /// //</u>	7. If Unit or CA/Agreement, Name and/or No.
	verse side	1 14 B: 15
of Well		San Juan 29-5 Unit 8. Well Name and No.
il Well X Gas Well Other		
of Operator lips Petroleum Company		SJ 29-5 Unit #52M
	Phone No. (include area code)	30-039-26310
5525 Highway 64, NBU 3004, Farmington, NM 87401 505-599-3454 Location of Well (Footage, Sec., T., R., M., or Survey Description) Unit I, 1450' FSL & 1080' FEL Section 29, T29N, R5W		10. Field and Pool, or Exploratory Area
		Basin Dakota and Blanco Mesaverde
		11. County or Parish, State
		Rio Arriba, NM
12. CHECK APPROPRIATE BOX(ES) TO INDIC.	ATE NATURE OF NOTICE, REPOR	RT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTIO	N
Notice of Intent Acidize	Deepen Product	tion (Start/Resume) Water Shut-Off
	Fracture Treat Reclama	
X Subsequent Report	New Construction Recomp	\(\bar{\sqrt{1}}\)
Casing Repair		
Final Abandonment Notice Change Plans		casting report
Convert to Injection	Plug Back Water I	Disposal
Hermined that the final site is ready for final inspection.) H w/6-1/4" bit to 3900'. Drilled out cement shoe is for 15 minutes each. Good test. Drilled ahead 061' with ECP set @ 5349' and DV tool @ 5346 for 2 ead w/150 sx (320 cf - 2.13 yield) Class H 35:65 P #/sx Gilsonite, 0.3% CD-32, 0.7% FL-52. Pumped ta ello-flake, 5#/sx Gilsonite, 0.3% FL-25. Displace loat held. et ECP w/1500 psi & dropped shifting tool & opened 0.93 yield)Type 3 cement - 35:65 POZ, 6% Bentonite, ilsonite, 0.4% FL-52, 0.02% Static free. Pumped ta aCl2, 0.25#/sx Cello-flake. Displace with 83 bbls	8061'. RIH w/4-1/2" 11 stage cement job. RU B. OZ, 6% Bentonite, 10#/sx il - 50 sx (63 cf - 1.27 d with 124 bbls H20. Plu DV tool. Cemented 2nd 3% KCL, 10#/sx CSE, 0.2 ail - 50 sx (870 cf - 1.	.6#, L-80 casing and set @ J to cement. Pumped 1st stage CSE, 0.25#/sx Cello-flake, yield) Class H, 0.25#/sx ug down @ 0215 hrs 4/26/00. stage Lead w/95 sx (176 cf - 5#/sx Cello-flake, 5#/sx 4 yield) Type 3 cement, 1%
ad full returns. Circulated 10 bbls good cement of	off of the DV tool from t	he first stage. ND BOP, set
lips, cut off casing. RD & released rig 0600 hrs	4/26/00. Will clean out	stage tool & cement, then
est the casing when completion rig moves in to com	plete the DK interval.	
reby certify that the foregoing is true and correct the (Profited Toped) Patsy Clugston	Title Sr. Rea	ulatory/Proration Clerk
7 curry crugston	Date 5/8/00	ACCEPTED FOR RECO
THIS SPACE FOR FEDER	AL OR STATE OFFICE USE	
ved by	Title	Date MAY 2 4 2000
ons of approval, if any, are attached. Approval of this notice does not warra	nt of Office	-Amminus viv
ons of approval, if any, are attached. Approval of this notice does not warra that the applicant holds legal or equitable title to those rights in the subject would entitle the applicant to conduct operations thereon.	nt or Office lease	-Anmin