Form 3160-5 (August 1999)

determined that the final site is ready for final inspection.)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVE	D
OMB NO. 1004-013	35
Expires: November 30	200

Э.	LCASC	201191	NO.	
NMN	M052	20		

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

6. If Indian, Allottee or Tribe Name

			0		
SUBMIT IN TRIPLICATE -	Other instructions	on reverse side		7. If Unit or C.	A/Agreement, Name and/or No.
SUBMIT IN TRIPLICATE - 1. Type of Well Oil Well X Gas Well Other		ON CON	12 13 15 15 15 15 15 15 15 15 15 15 15 15 15	San Juan 2 8. Well Name	
2. Name of Operator Phillips Petroleum Company				SJ 29-6 Ur 9. API Well N	
3a. Address <u>5525 Highway 64, NBU 3004, Farming</u> t	on, NM 87401	3b. Phone No. Hinglyde ar 505-599-3454	a com	30-039-263	Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Surve Unit C, 1190' FNL & 1850' FWL Section 26, T29N, R6W	y Description)			Blanco Mes Basin Dako 11. County or Rio Arriba	Parish, State
12. CHECK APPROPRI	ATE BOX(ES) TO I	NDICATE NATURE OF NO	TICE, REPORT,		
TYPE OF SUBMISSION		ТҮР	E OF ACTION		
Notice of Intent	Acidize	Deepen		(Start/Resume)	Water Shut-Off
X Subsequent Report	Alter Casing Casing Repair	Fracture Treat New Construction	Recomplet		Well Integrity Other
Final Abandonment Notice	Change Plans Convert to Inject	Plug and Abandon ion Plug Back	Temporari Water Dis	ly Abandon posal	7" castrig report
 Describe Proposed or Coommpleted Operation (clear If the proposal is to deepen directionally or recomp Attach the Bond under which the work will be per 	lete horizontally, give s	ubsurface locations and measur	ed and true verti	cal depths of all	pertinent markers and zones.

RIH w/8-3/4" bit & tagged up to 300'. Drilled out cement to 333'. Drilled ahead to 3762'. Circ. hole. RIH w/7", 20#, J-55 casing and landed @ 3762'. RU to cement. Pumped 500 sx (1185 cf - 211 bbls slurry) Type 3 35:65 POZ, 6% Bentonite, 10#/sx CSE, 1/4#/sx Cello-flake, 5#/sx Gilsonite, 3% KCL, 0.4% FL-25, 0.02#/sx Static free.

following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has

Tail - 50 sx (70 cf - 12.46 bbls slurry)Type 3, 1% CaCl2, 1/4#/sx Cello-flake. Displaced with 150.7 bbls H20. Plug down at 2200 hrs 6/20/00. Float held. Circulated 13 bbsl (73 cf) cement to surface. ND BOP & set slips and cut off casing. NU BOP & manifold. PT - good test.

14. I hereby certify that the foregoing is true and correct Name (Printed/Typkd)	Title		
Patsy Clugston		Sr. Regulato	ory/Proration Clerk
+ also Clust	Date	6/21/00	ACCEPTED FOR RECORD
THIS SPACE FOR FED	ERAL OR ST	ATE OFFICE USE	
Approved by	Title		Star 0 2 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5
Conditions of approval, if any, are attached. Approval of this notice does not we certify that the applicant holds legal or equitable title to those rights in the subj which would entitle the applicant to conduct operations thereon.			FARMING TON HILLD OFFICE

Title 18 U.S.C. Section 1001, and Title 43 U.S.C. Section 1212, makes it a crime for any person knowingly and willfully to make to any department or and the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.