Form 3160-5 (August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED OMB NO. 1004-0135 Expires: November 30, 2000

		N Commence of the Commence of
SUNDRY NOTICES AND REPORTS ON V	WELLS VOY	NM-03040A
Do not use this form for proposals to drill or to re-ent abandoned well. Use Form 3160-3 (APD) for such pro	ter and C 10 3 10 17	6. If Indian, Allottee or Tribe Name
SUBMIT IN TRIPLICATE - Other instructions on	On CON CON	7. If Unit or CA/Agreement, Name and/or No.
Type of Well Oil Well X Gas Well Other	DIST. DIV	San Juan 29-6 Unit 8. Well Name and No.
Name of Operator Phillips Petroleum Company	Corner 70	S.J 29-6 Unit #86M 9. API Well No.
5525 Highway 64, NBU 3004, Farmington, NM 87401	Phone No Circlistriarea 505-599-3454	10. Field and Pool, or Exploratory Area
Location of Well (Footage, Sec., T., R., M., or Survey Description) Unit C, 1190' FNL & 1843' FWL Section 27, T29N, R6W		Basin Dakota and Blanco Mesaverde 11. County or Parish, State
Section 27, 129N, NOW		Rio Arriba. NM
12. CHECK APPROPRIATE BOX(ES) TO INDIC	ATE NATURE OF NOTION	CE, REPORT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE	OF ACTION
Notice of Intent Acidize	Deepen Fracture Treat	Production (Start/Resume) Water Shut-Off Reclamation Well Integrity
X Subsequent Report Casing Repair	New Construction	Recomplete X Other Spud Repor
Final Abandonment Notice Change Plans Convert to Injection	Plug and Abandon Plug Back	Temporarily Abandon Water Disposal
Describe Proposed or Coommpleted Operation (clearly state all pertinent details, If the proposal is to deepen directionally or recomplete horizontally, give subsur Attach the Bond under which the work will be performed or provide the Bond following completion of the involved operations. If the operation results in a metasting has been completed. Final Abandonment Notices shall be filed only addetermined that the final site is ready for final inspection.)	No. on file with BLM/BL	A. Required subsequent reports shall be filed within 30 days
Attach the Bond under which the work will be performed or provide the Bond following completion of the involved operations. If the operation results in a m testing has been completed. Final Abandonment Notices shall be filed only all determined that the final site is ready for final inspection.) 6/7/00 MIRU Key Energy #47. Spud 12-1/4" hole @ 10 hole. RIH w/9-5/8", 36#, K-55 casing and set @ 33 slurry) Type 3 cement, 1/4#/sx Cello-flake, 2% CaC bbls. Plug down @ 0145 hrs, circulated 8 bbls (44	No. on file with BLM/BL ultiple completion or recom fiter all requirements, include 630 hrs 6/7/00. It 5'. RU to cement 12 mixed at 14.5 cf) cement to su	A. Required subsequent reports shall be filed within 30 days upletion in a new interval, a Form 3160-4 shall be filed once the completed, and the operator has been completed, and the operator has brilled ahead to 335'. Circulated Pumped 225 sx (317 cf - 56.46 bbls ppg. 1.41 yield. Displaced with 23.5
Attach the Bond under which the work will be performed or provide the Bond following completion of the involved operations. If the operation results in a m testing has been completed. Final Abandonment Notices shall be filed only all determined that the final site is ready for final inspection.) 6/7/00 MIRU Key Energy #47. Spud 12-1/4" hole @ 16 hole. RIH w/9-5/8", 36#, K-55 casing and set @ 33 hole. The complete of the complete of the provided Herman Spud 14/4 (cr. Cello-flake 2% CaC.	No. on file with BLM/BL ultiple completion or recom fiter all requirements, include 630 hrs 6/7/00. It 5'. RU to cement 12 mixed at 14.5 cf) cement to su	A. Required subsequent reports shall be filed within 30 days upletion in a new interval, a Form 3160-4 shall be filed once the completed, and the operator has been completed, and the operator has brilled ahead to 335'. Circulated Pumped 225 sx (317 cf - 56.46 bbls ppg. 1.41 yield. Displaced with 23.5
Attach the Bond under which the work will be performed or provide the Bond following completion of the involved operations. If the operation results in a m testing has been completed. Final Abandonment Notices shall be filed only all determined that the final site is ready for final inspection.) 6/7/00 MIRU Key Energy #47. Spud 12-1/4" hole @ 10 hole. RIH w/9-5/8", 36#, K-55 casing and set @ 33 slurry) Type 3 cement, 1/4#/sx Cello-flake, 2% CaC bbls. Plug down @ 0145 hrs, circulated 8 bbls (44	No. on file with BLM/BL ultiple completion or recom filer all requirements, include 630 hrs 6/7/00. If 5'. RU to cement 12 mixed at 14.5; cf) cement to suid d test.	A. Required subsequent reports shall be filed within 30 days upletion in a new interval, a Form 3160-4 shall be filed once the filed once the filed control of the filed once the filed on
Attach the Bond under which the work will be performed or provide the Bond following completion of the involved operations. If the operation results in a metating has been completed. Final Abandonment Notices shall be filed only addetermined that the final site is ready for final inspection.) 6/7/00 MIRU Key Energy #47. Spud 12-1/4" hole @ 10 hole. RIH w/9-5/8", 36#, K-55 casing and set @ 33 slurry) Type 3 cement, 1/4#/sx Cello-flake, 2% CaC bbls. Plug down @ 0145 hrs, circulated 8 bbls (44 casing and manifold to 200 psi then 1500 psi - Good APD / ROW	No. on file with BLM/BL ultiple completion or recom filer all requirements, include 630 hrs 6/7/00. If 5'. RU to cement 12 mixed at 14.5; cf) cement to suid d test.	A. Required subsequent reports shall be filed within 30 days upletion in a new interval, a Form 3160-4 shall be filed once the
Attach the Bond under which the work will be performed or provide the Bond following completion of the involved operations. If the operation results in a metasting has been completed. Final Abandonment Notices shall be filed only at determined that the final site is ready for final inspection.) 6/7/00 MIRU Key Energy #47. Spud 12-1/4" hole @ 16 hole. RIH w/9-5/8", 36#, K-55 casing and set @ 33 slurry) Type 3 cement, 1/4#/sx Cello-flake, 2% CaC bbls. Plug down @ 0145 hrs, circulated 8 bbls (44 casing and manifold to 200 psi then 1500 psi - Goo	No. on file with BLM/BL ultiple completion or recom fler all requirements, include 630 hrs 6/7/00. It 5'. RU to cement 12 mixed at 14.5 cf) cement to suid d test. PROCESS	A. Required subsequent reports shall be filed within 30 days upletion in a new interval, a Form 3160-4 shall be filed once the filed once the filed control of the filed once the filed on
Attach the Bond under which the work will be performed or provide the Bond following completion of the involved operations. If the operation results in a metasting has been completed. Final Abandonment Notices shall be filed only addetermined that the final site is ready for final inspection.) 6/7/00 MIRU Key Energy #47. Spud 12-1/4" hole @ 10 hole. RIH w/9-5/8", 36#, K-55 casing and set @ 33 slurry) Type 3 cement, 1/4#/sx Cello-flake, 2% CaC bbls. Plug down @ 0145 hrs, circulated 8 bbls (44 casing and manifold to 200 psi then 1500 psi - Good APD / ROW APD / ROW APD / ROW Patsy Clugston	No. on file with BLM/BL ultiple completion or recom fier all requirements, include 630 hrs 6/7/00. It 5'. RU to cement 12 mixed at 14.5 cf) cement to suid d test. PROCESS Title Date 6/	A. Required subsequent reports shall be filed within 30 days upletion in a new interval, a Form 3160-4 shall be filed once fing reclamation, have been completed, and the operator has Drilled ahead to 335'. Circulated Drilled ahead to 335'. Circulated Pumped 225 sx (317 cf - 56.46 bbls ppg, 1.41 yield. Displaced with 23.5 rface. WOC. NU WH & BOP. PT BOP, Sr. Regulatory/Proration Clerk 12/00 ACCEPTED FOR RECO
Attach the Bond under which the work will be performed or provide the Bond following completion of the involved operations. If the operation results in a m testing has been completed. Final Abandonment Notices shall be filed only all determined that the final site is ready for final inspection.) 6/7/00 MIRU Key Energy #47. Spud 12-1/4" hole @ 16 hole. RIH w/9-5/8", 36#, K-55 casing and set @ 33 slurry) Type 3 cement, 1/4#/sx Cello-flake, 2% CaC bbls. Plug down @ 0145 hrs, circulated 8 bbls (44 casing and manifold to 200 psi then 1500 psi - Goo APD / ROW 4. I hereby certify that the foregoing is true and correct Name (Print A/Typ)d) Patsy Clugston THIS SPACE FOR FEDE	No. on file with BLM/BL ultiple completion or recom fier all requirements, include 630 hrs 6/7/00. It 5'. RU to cement 12 mixed at 14.5 cf) cement to suid d test. PROCESS Title Date 6/	A. Required subsequent reports shall be filed within 30 days upletion in a new interval, a Form 3160-4 shall be filed once fing reclamation, have been completed, and the operator has Drilled ahead to 335'. Circulated Pumped 225 sx (317 cf - 56.46 bbls ppg, 1.41 yield. Displaced with 23.5 rface. WOC. NU WH & BOP. PT BOP, Sr. Regulatory/Proration Clerk 12/00 ACCEPTED FOR RECO
Attach the Bond under which the work will be performed or provide the Bond following completion of the involved operations. If the operation results in a metsting has been completed. Final Abandonment Notices shall be filed only at determined that the final site is ready for final inspection.) 6/7/00 MIRU Key Energy #47. Spud 12-1/4" hole @ 10 hole. RIH w/9-5/8", 36#, K-55 casing and set @ 33 slurry) Type 3 cement, 1/4#/sx Cello-flake, 2% CaC bbls. Plug down @ 0145 hrs, circulated 8 bbls (44 casing and manifold to 200 psi then 1500 psi - Goo APD / ROW 14. I hereby certify that the foregoing is true and correct Name (Printed/Typed) Patsy Clugston	No. on file with BLM/BL ultiple completion or recom file all requirements, include 630 hrs 6/7/00. It 5'. RU to cement 12 mixed at 14.5 cf) cement to suid d test. PROCESS Title Date 6/ RAL OR STATE OFF Title Tant of Office	A. Required subsequent reports shall be filed within 30 days upletion in a new interval, a Form 3160-4 shall be filed once fing reclamation, have been completed, and the operator has Drilled ahead to 335'. Circulated Drilled ahead to 335'. Circulated Pumped 225 sx (317 cf - 56.46 bbls ppg, 1.41 yield. Displaced with 23.5 rface. WOC. NU WH & BOP. PT BOP, Sr. Regulatory/Proration Clerk 12/00 ACCEPTED FOR RECO