1-M.M.J.C.C.-Aztec 1-El Paso Natural (Galloway) 1-L. G. Truby 1-W. R. Johnston 1-File

Ъb

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

OIL CON. COM.

					MULTI	-POINT I	BACK PRE	SSURE TI	EST FOR GA	s wells		Revised 12-1-5	
Poo	ol	Blance) 										
		•											
Con	npany_	Pacif	lc Nor	thwest	Pipel	ine Corp	Lease 2	9-7		Wel	1 No	57-11	
												Pipeline Corp.	
Cas	5 ing_ 7	$\frac{1/2}{5/8}$	/t	I	.D.	Se	55. et at 32	16	Perf. 487	4	To_ 5 454	<u>.</u>	
									Perf				
Pro	ducin	g Thru:	: Ca	.sing		Tu	ibing	xx	Type Weingle-Brade	ell <u>s</u>	ingle		
Dat	e of	Complet	cion:_		<u>.</u>	Packe	r no	Si	ingle-Brade Reserve	enhead-G. oir Temp	G. or 0	.0. Dual	
							OBSER	VED DATA					
Tes	ted Th	nrough	(Pr &	¥% r) (Choke)	(WXXXX)	Shut	in 7 de	ys	Туре Тар	s		
				Flow D				Tubing			Data		
No.		rover) Line)	(Ch	oke) fice)	Press	. Diff.	,		Temp.			Duration of Flow	
SI		Size	S	ize	psig	h _w	°F.	psig	°F.	psig	[⊃] F•	Hr.	
1. 2. 3. 4. 5.			3/4		348		74	348	74	872		3	
3.			 		-								
4.													
	!		L	<u>.</u>	+	1					1		
 -	Co	effici	.ent		P	ressure	FLOW CAI Flow	Temp.	ONS Gravity	y Compress. Rate of Flow			
No.	(24-Hour) 7/h _w			Pf	<u> </u>		tor t	Factor	Factor F _{DV}		Q-MCFPD @ 15.025 psia		
1.	14.16	_		VW	- 1	360	•9868	t	F _g	1.033		4993	
1. 2. 3. 4. 5.													
3. 4.													
5.									·				
						PR	ESSURE C	CALCULAT	IONS				
las i	Liquid	l Hvdro	ca rboi	n Rati	0		cf/bbl.		Speci	ific Gravi	t.v. Sena	rator Gas	
Gas Liquid Hydrocarbon Ratio cf/bbl. Gravity of Liquid Hydrocarbons deg.								Specific Gravity Separator Gas Specific Gravity Flowing Fluid					
Fc				(1-e ^{-s} ∑			-	^Р с	1121	_Pc	1256.6	
	D								884	γ			
No.	$P_{\mathbf{W}}$		P	2 F	Q	$(F_cQ)^2$	(F	$(cQ)^2$	P _w 2	$P_c^2 - P_w^2$	Ca	1. Pw	
	Pt (psia)					(1	_e-s)			P	$\begin{array}{c c} 1. & P_{\mathbf{w}} \\ \hline P_{\mathbf{C}} & \end{array}$	
1. 2.				- · ·					781.5	475.1	-	2.64	
3.7													
4. 5.				_									
	olute	Potent	ial:	10.3	41		MCFPD:	n .7	5/2.0710	+			
COM	PANY F	aci fi c	Nort!	huest	Pineli	e Corpo	retion				· 		
ADD)	пвоо <u>≪.</u> NT and	TITLE	C, R	. Wagn	er - K	ngton, N	Enginee	r	 				
WIT	NESSEL	Tom	Grant	- K	nginee	r ,	_						
COM	PANY	El Pa	so Na	cural	Gas Cor	ibenA	ATT A	ARKS			ار ا المامة ا	1601	
							1 frint	P21(17F)		1	123 Table	:357	

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q \equiv Actual rate of flow at end of flow period at W. H. working pressure (P_W). MCF/da. @ 15.025 psia and 60° F.
- P_c 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- Pw- Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- P_{f} Meter pressure, psia.
- hw- Differential meter pressure, inches water.
- F_{g} Gravity correction factor.
- F_t Flowing temperature correction factor.
- $\mathbf{F}_{\mathbf{pv}}\mathbf{I}$ Supercompressability factor.
- n I Slope of back pressure curve.

Note: If $P_{\mathbf{W}}$ cannot be taken because of manner of completion or condition of well, then $P_{\mathbf{W}}$ must be calculated by adding the pressure drop due to friction within the flow string to $P_{\mathbf{t}}$.

OIL CONSERVA	TION COMMI	SSION					
AZTEO DISTRICT OFFICE							
No. Copies Discolated 3							
Operator							
Santa Fe	1						
Proration Office	en i de de la companya de la company						
State Land Office							
U. S. G. S.	/						
Transporter							
File	/	2					