

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*

(See other In-
structions on
reverse side)

Form approved.
Budget Bureau No. 1004-0137
Expires August 31, 1985

WELL COMPLETION OR RECOMPLETION REPORT AND LOG *

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ Other ☐
b. TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESER. ☐ Other ☐

2. NAME OF OPERATOR
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR
P. O. Box 4289, Farmington, NM 87499

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface 1790'S 1450'E

At top prod. interval reported below 4626'

At total depth 5674'

14. PERMIT NO.

DATE ISSUED

7. UNIT AGREEMENT NAME

San Juan 29-7 Unit

8. FARM OR LEASE NAME

San Juan 29-7 Unit

9. WELL NO.

52A

10. FIELD AND POOL, OR WILDCAT

Blanco Mesa Verde

11. SEC. T. R. M., OR BLOCK AND SURVEY OR AREA

Sec. 7, T-29-N. R-7-W
NMPM

12. COUNTY OR PARISH

Rio Arriba

13. STATE

NM

15. DATE SPUDDED 12-22-85 16. DATE T.D. REACHED 1-2-86 17. DATE COMPL. (Ready to prod.) 1-27-86 18. ELEVATIONS (DP, RNB, RT, GR, ETC.)* 6254' GL 19. ELEV. CASINGHEAD 6254'

20. TOTAL DEPTH, MD & TVD 5674' 21. PLUG BACK T.D., MD & TVD 5644' 22. IF MULTIPLE COMPL., HOW MANY* One 23. INTERVALS DRILLED BY Rotary 24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)* 4626-5564' (Blanco Mesa Verde) 25. WAS DIRECTIONAL SURVEY MADE No

26. TYPE ELECTRIC AND OTHER LOGS RUN Ind. Electrolog Gamma Ray; Comp. Densilog Gamma Ray; CBL-GR-CCL; Differential Temp. Log GR; Temp S. 27. WAS WELL CORED No

28. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
9 5/8"	32.3#	221'	12 1/4"	142 cu ft	
7"	20.0#	3354'	8 3/4"	402 cu ft	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
4 1/2"	3207'	5672'	424 cu ft		2 3/8"	5543'	

30. TUBING RECORD

31. PERFORATION RECORD (Interval, size and number) Pressure test

csg. to 3500 psi-ok. Perf'd (Lower Pt. L.)
5305, 5313, 5322, 5349, 5372, 5390, 5405,
5431, 5442, 5468, 5474, 5495, 5554, 5564,
w/14 SPZ. 2nd stage (Mass. Pt. L.) 4978,
5005, 5011, 5047, 5063, 5069, 5075, 5090,

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
5305-5564'	59,000# 20/40 sand & 82,200 gals slickwater
4978-5281'	61,500# 20/40 sand & 138,860 gal slickwater

* Continued Perf's listed on back pg. 1 PRODUCTION 4626-4931' 52,000# 20/40 sand & 117,515 gal

DATE FIRST PRODUCTION 1-20-86 PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump) Flowing - when connected. Capable of Comm. HC to be tested. WELL STATUS (Producing, Shut in) Shut in

DATE OF TEST	HOURS TESTED	CHOKE SIZE	PRD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO
1-27-86	SI 7 Days	0		0	0	0	0
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HR RATE	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)	
SI 332	SI 720		No Flow	No Flow	No Flow	0	

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

Shut in to be Sold

TEST WITNESSED BY

John Easley

35. LIST OF ATTACHMENTS

Temp Survey

ACCEPTED FOR RECORD

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED

TITLE

Drilling Clerk

DATE

1-28-86

*(See Instructions and Spaces for Additional Data on Reverse Side)

GEOLOGIC MARKERS

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
					MEAS. DEPTH	TRUE VERT. DEPTH
Chacra	4007'	4649'	Gry fn grn silty, glauconitic sd stone w/drk gry shale	Chacra	4007'	
Mesa Verde	4649'	4815'	Gry, fine-grn, dense sil ss., carb sh & coal	Mesa Verde	4649'	
Menefee	4815'	5193'	Gry, fine-grn s, carb sh & coal	Menefee	4815'	
Point Lookout	5193'	5672'	Gry, very fine sil ss w/frequent sh breaks	Point Lookout	5193'	
=====						
* Continued Perf's:						
5119, 5131, 5145, 5151, 5157, 5202, 5208, 5214, 5220, 5226, 5235, 5241, 5247, 5262, 5281 w/PZ SPZ.						
3rd stage (C.H. & Menefee) 4626, 4652, 4658, 4676, 4686, 4723, 4740, 4754, 4762, 4768, 4774, 4789,						
4795, 4801, 4808, 4834, 4840, 4854, 4902, 4931 w/1 SPZ.						
=====						