

State of New Mexico  
Energy, Minerals and Natural Resources Department  
Oil Conservation Division

Sundry Notices and Reports on Wells

1. Type of Well  
GAS

2. Name of Operator  
**BURLINGTON RESOURCES** OIL & GAS COMPANY

3. Address & Phone No. of Operator  
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M  
1525' FNL, 120' FWL, Sec.16, T-29-N, R-7-W, NMPM, Rio Arriba County, NM

API # (assigned by OCD)  
30-039-25825

5. Lease Number

6. State Oil&Gas Lease #  
B-10037-58-NM

7. Lease Name/Unit Name  
San Juan 29-7 Unit

8. Well No.  
#92B

9. Pool Name or Wildcat  
Blanco Mesaverde

10. Elevation:

| Type of Submission                                    | Type of Action                                                       |
|-------------------------------------------------------|----------------------------------------------------------------------|
| <input type="checkbox"/> Notice of Intent             | <input type="checkbox"/> Abandonment                                 |
| <input checked="" type="checkbox"/> Subsequent Report | <input type="checkbox"/> Recompletion                                |
| <input type="checkbox"/> Final Abandonment            | <input type="checkbox"/> Plugging Back                               |
|                                                       | <input type="checkbox"/> Casing Repair                               |
|                                                       | <input type="checkbox"/> Altering Casing                             |
|                                                       | <input checked="" type="checkbox"/> Other - Spud, casing, and cement |

13. Describe Proposed or Completed Operations

8-24-98 MIRU. Spud well @ 1:30 pm 8-24-98. Drill to 228'. Circ hole clean. TOOH. TIH w/5 jts 9 5/8" 32.3# WC-50 ST&C csg, set @ 218'. Cmt'd w/180 sx Class "B" neat cmt w/3% calcium chloride, 0.25 pps Flocele (212 cu ft). Circ 15 bbl cmt to surface. WOC. NU BOP. PT BOP & csg to 600 psi/30 min., OK. Drilling ahead.

8-26-98 Drill to intermediate TD @ 3365'. Circ hole clean. TOOH.

8-27-98 TIH w/82 jts 7" 20# J-55 ST&C csg, set @ 3354'. Cmt'd w/261 sx Class "B" neat cmt w/3% sodium metasilicate, 0.5 pps Flocele, 7 pps Kolite (760 cu ft). Tailed w/93 sx Class "B" 50/50 poz w/2% calcium chloride, 2% gel, 0.5 pps Flocele, 7 pps Kolite (130 cu ft). Circ 15 bbl cmt to surface. WOC. ND BOP. PT BOP & csg to 1500 psi/30 min., OK. Drilling ahead.

8-29-98 Drill to TD @ 5675'. Circ hole clean. TOOH. TIH w/58 jts 4 1/2" 10.5# J-55 ST&C csg, set @ 5670'. Lnr top @ 3180'. Cmt'd w/261 sx Class "B" 50/50 poz w/2% gel, 0.25 pps Flocele, 5 pps Kolite, 0.5% fluid loss, 0.1% dispersant (358 cu ft). ND BOP. NU WH. RD. Rig released.

SIGNATURE Nancy Altman for Regulatory Administrator September 1, 1998

vkh

(This space for State Use)

Approved by ORIGINAL SIGNED BY CHARLIE Y. PERDUE Title DEPUTY OIL & GAS INSPECTOR, DIST. #3 Date SEP 3 1998